


1 LOCATION OF WATER WELL:	Fraction County: Butler	SE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 9	Township Number T 26 S	Range Number R 3 E/W	
Distance and direction from nearest town or city street address of well if located within city? 2 1/2 miles East Beeson on 254 3/4 North west side						
2 WATER WELL OWNER:	Dale E Rodman 2740 N. Wilderness Ct Wichita, KS 67226		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:						
4 DEPTH OF COMPLETED WELL	68	ft. ELEVATION:				
Depth(s) Groundwater Encountered	55	ft. 2.	ft. 3. 2/19/94			
WELL'S STATIC WATER LEVEL	55	ft. below land surface measured on mo/day/yr				
Pump test data: Well water was	ft. after	hours pumping	gpm			
Est. Yield	60	ft. after	hours pumping			
Bore Hole Diameter	10	ft., and	in. to			
WELL WATER TO BE USED AS:	5 Public water supply 1 Domestic 2 Irrigation	8 Air conditioning 6 Oil field water supply 4 Industrial	11 Injection well 9 Dewatering	12 Other (Specify below)		
Was a chemical/bacteriological sample submitted to Department? Yes	No, If yes, mo/day/yr sample was submitted					
Water Well Disinfected?	Yes	No				
5 TYPE OF BLANK CASING USED:	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass			CASING JOINTS: Glued Clamped Welded Threaded		
1 Steel 1 PVC	3 RMP (SR) 4 ABS	8 Concrete tile 9 Other (specify below)				
Blank casing diameter	12	in. to	ft., Dia	in. to	ft., Dia in. to ft.	
Casing height above land surface	12	in., weight	lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass 6 Concrete tile			10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	8 RMP (SR) 9 ABS				
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut			8 Saw cut 9 Drilled holes 10 Other (specify)		
1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	48	ft. to 68	ft. to	ft. to ft.	
SCREEN-PERFORATED INTERVALS:	From	48	ft. to 68	ft. to	ft. to ft.	
GRAVEL PACK INTERVALS:	From	20	ft. to 68	ft. to	ft. to ft.	
From	ft. to	ft. to	ft. to	ft. to	ft. to ft.	
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	Bentonite	4 Other		
Grout Intervals:	From 3	ft. to 20	ft. to	ft. to	ft. to ft.	
What is the nearest source of possible contamination:	7 Pit privy 8 Sewage lagoon 9 Feedyard			10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Creek		
Direction from well?	How many feet? 200+					
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	2	dirt				
2	10	yellow clay				
10	12	green shale				
12	30	grey shale				
30	68	shaly lime				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **2/19/94** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **493** This Water Well Record was completed on (mo/day/yr) **7/16/94** by (signature) **Henry Jensen**
under the business name of **Reiserer Well Services**