


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction NE 1/4	NE 1/4	NE 1/4	Section Number 25	Township Number T 26 S	Range Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 4255 SW Santa Fe Lake Road Towanda, Kansas 67144							
2 WATER WELL OWNER:		Terry Patrick		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #		4255 Santa Fe Lake Road		Application Number:			
City, State, ZIP Code		Towanda, Kansas 67144					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 50 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 6-11-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9 in. to 80 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 7 PVC	6 Asbestos-Cement	8 Concrete tile	CASING JOINTS: Glued X Clamped Welded Threaded
Blank casing diameter		5	in. to 50	ft., Dia	in. to ft., Dia	in. to ft.	
Casing height above land surface		24	in., weight	lbs./ft. Wall thickness or gauge No. SDR26			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 2 Brass		3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	11 None (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped	7 Torch cut	8 Saw cut 9 Drilled holes	10 Other (specify) 11 None (open hole)	
SCREEN-PERFORATED INTERVALS:		From 50 ft.	to 80 ft.	From ft.	to ft.	From ft.	to ft.
GRAVEL PACK INTERVALS:		From 20 ft.	to 80 ft.	From ft.	to ft.	From ft.	to ft.
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:		From 4 ft. to 20 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.		
What is the nearest source of possible contamination:							
1 Septic tank 2 Sewer lines		4 Lateral lines 5 Cess pool	7 Pit privy 8 Sewage lagoon	10 Livestock pens 11 Fuel storage	14 Abandoned water well 15 Oil well/Gas well		
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage 13 Insecticide storage	16 Other (specify below)		
Direction from well?							
FROM TO LITHOLOGIC LOG				FROM	TO	PLUGGING INTERVALS	
0	6	Soil					
6	45	Clay & shale					
45	50	Sand & shale					
50	80	Shale w/lime stks					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-94 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 171				This Water Well Record was completed on (mo/day/yr) 6-11-94 by (signature) Ref. 3094			
under the business name of G & S Drilling							

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.