


1 LOCATION OF WATER WELL: Butler	FRACTION NE 1/4 SE 1/4 NE 1/4	Section Number 25	Township Number T 26 S	Range Number R 3E E/W
Distance and direction from nearest town or city street address of well if located within city? 2 miles W., 2.3 miles S., 200' West of Towanda, Kansas				
2 WATER WELL OWNER: NEUMANN, Harold	RR#, ST. ADDRESS, BOX #: Rt. 1 Box 54A	Board of Agriculture, Division of Water Resource 67144		
CITY, STATE, ZIP CODE: Towanda, Kansas				Application Number: _____
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 71 ft.	ELEVATION: basement floor ft. 3 ft.		
	Depth(s) groundwater Encountered 1	FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 05/17/1994		
	WELL'S STATIC WATER LEVEL 30			
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft. and in. to ft.			
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
	Water Well Disinfected? Yes X No			
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below)	CASING JOINTS: Glued X Clamped Welded Threaded	
Blank casing Diameter 6 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 36 in., weight lbs. / ft.			Wall thickness or gauge No. 7 PVC 10 Asbestos-cement	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	11 other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot 2 Louvered shutter 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut		8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: from ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.	2 Cement grout	3 Bentonite	4 Other 10 Livestock pens 14 Abandon water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard			
Direction from well? South	How many feet? 20			
FROM TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		0	10	cement grout
		10	30	bentonite hole plug
		30	71	chlorinated sand and gravel
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) <u>plugged</u> under my jurisdiction and was completed on (mo/day/year) 05/17/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 05/19/94 . Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick				