

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BUTLER		NW 1/4 NW 1/4 NE 1/4	36	T 26 S	R 3 E
Distance and direction from nearest town or city street address of well if located within city? 3 mi. South and 2 1/2 mi. West of Towanda					
2 WATER WELL OWNER: CHRIS DAVIS					
RR#, St. Address, Box # : RR#1					
City, State, ZIP Code : TOWANDA, KS. 67144					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 100 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 46 ft. below land surface measured on mo/day/yr 4/2/92			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 80 gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 10 in. to ft., and in. to ft.			
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 <u>Lawn and garden only</u> 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 <u>PVC</u> 4 <u>ABS</u> 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 <u>Mill slot</u> 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 110 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other					
Grout Intervals: From 3 ft. to ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 <u>Sewage lagoon</u> 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? down slope How many feet? 100+					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	corr			
3	15	broken rock			
15	22	red rock			
22	40	shale			
40	68	gray lime			
68	73	shale			
73	90	shale lime			
90	100	red bed			
100	110	yellow lime water			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/2/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) under the business name of Kansas Well Drilling by (signature) James Bismar					