


1	LOCATION OF WATER WELL: Butler	FRACTION SW 1/4 SW 1/4 SE 1/4	Section Number 36	Township Number T 26 S	Range Number R 3E E/W	
Distance and direction from nearest town or city street address of well if located within city?						
2	WATER WELL OWNER: CAPPS, Wesley	RR#, ST. ADDRESS, BOX #: RR #1	Board of Agriculture, Division of Water Resource			
CITY, STATE, ZIP CODE: Augusta, Kansas		67010	Application Number:			
3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4	DEPTH OF COMPLETED WELL Depth(s) groundwater Encountered 110 ft.	ELEVATION: ft. below land surface measured on mo/day/yr 50 ft. below land surface measured on 07/01/1992	3 ft.	
WELL'S STATIC WATER LEVEL Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping Bore Hole Diameter 12 in. to 110 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No						
5	TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS					CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded
Blank casing Diameter 5 in. to 50 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.29 lbs. / ft.						Wall thickness or gauge No. 10 Asbestos-cement .214
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile						7 PVC 8 RMP (SR) 9 ABS 11 other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot 5 Gauzed wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped 7 Torch cut						8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
SCREEN-PERFORATION INTERVALS: from 50 ft. to 110 ft., From ft. to ft. from ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: from 24 ft. to 110 ft., From ft. to ft. from ft. to ft., From ft. to ft.						ft. to ft.
6	GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft.						ft. to ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard						10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? Northeast						How many feet? 150
FROM TO LITHOLOGIC LOG			FROM TO	PLUGGING INTERVALS		
0	3	topsoil				
3	62	brown shale				
62	110	grey shale				
7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/01/1992 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/23/92 . Under the business name of Harp Well & Pump Service, Inc. by (signature) <i>Jane Frederick</i>					