

## 1 LOCATION OF WATER WELL:

Fraction

SE  $\frac{1}{4}$  NE  $\frac{1}{4}$  SW  $\frac{1}{4}$ 

Section Number

24

Township Number

T 26 S

Range Number

R 30 EW

County: **Butler**  
Distance and direction from nearest town or city street address of well, if located within city?

3 - W

2 - S of Towanda

67002

Board of Agriculture, Division of Water Resources  
Application Number:

## 2 WATER WELL OWNER:

**Ron Dow**

526 Boylan Andover Kan

RR#, St. Address, Box #

City, State, ZIP Code

## 3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL ft. ELEVATION:

Depth(s) Groundwater Encountered 145 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 60 gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 9/16 in. to ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

## 5 TYPE OF BLANK CASING USED:

5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR)  
2 PVC 4 ABS6 Asbestos-Cement 9 Other (specify below)  
7 Fiberglass

Welded Threaded

Blank casing diameter 5 in. to 50 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 18 in., weight 160 lbs./ft. Wall thickness or gauge No. 12.14

## TYPE OF SCREEN OR PERFORATION MATERIAL:

7 PVC 10 Asbestos-cement

1 Steel 3 Stainless steel  
2 Brass 4 Galvanized steel5 Fiberglass 8 RMP (SR)  
6 Concrete tile 9 ABS11 Other (specify)  
12 None used (open hole)

## SCREEN OR PERFORATION OPENINGS ARE:

5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
6 Wire wrapped 9 Drilled holes1 Continuous slot 3 Mill slot  
2 Louvered shutter 4 Key punched

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 50 ft. to 164 ft., From ft. to ft., From ft. to ft.

From ft. to ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.

From ft. to ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

How many feet?

Direction from well?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 4 Soil

4 18 Clay

18 25 Clay + Rock

25 30 Clay

30 167 Shale + Limestone

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/4/94 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/yr) 8/26/94

under the business name of **Winter Well Drill** by (signature) **Chad Winter**