

LOCATION OF WATER WELL:

Fraction

County: BUTLERSE 1/4 SE 1/4SE 1/4

Section Number

Township Number

Range Number

Distance and direction from nearest town or city street address of well if located within city?

1/2 WEST of TOWANDA on 254 N Side of Hwy.

WATER WELL OWNER:

J M RICKERSON

RR#, St. Address, Box #


RR#1

City, State, ZIP Code

TOWANDA KANSAS

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH  
AN "X" IN SECTION BOX:4 DEPTH OF COMPLETED WELL ..... 50 ft. ELEVATION: .....Depth(s) Groundwater Encountered 1. 18' ft. 2. ..... ft. 3. ..... ft.WELL'S STATIC WATER LEVEL 30' ft. below land surface measured on mo/day/yr 6-24-82

Pump test data: Well water was ..... ft. after ..... hours pumping ..... gpm

Est. Yield 20 gpm: Well water was ..... ft. after ..... hours pumping ..... gpmBore Hole Diameter 12 in. to 50 in. and ..... in. to ..... ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation wellWas a chemical/bacteriological sample submitted to Department? Yes ..... No X ..... If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)  
2 PVC 4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued X Clamped .....

Welded .....

Threaded .....

Blank casing diameter 8" in. to 50' ft., Dia ..... in. to ..... ft., Dia ..... in. to ..... ft.Casing height above land surface 18' in., weight ..... S.D.R. 26 lbs./ft. Wall thickness or gauge No. ....

6 TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS

PVC

10 Asbestos-cement

11 Other (specify) .....

12 None used (open hole) .....

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .....

SCREEN-PERFORATED INTERVALS: From ..... 30' ft. to ..... 50 ft., From ..... ft. to ..... ft.

From ..... ft. to ..... ft., From ..... ft. to ..... ft.

GRAVEL PACK INTERVALS: From ..... 4' ft. to ..... 14' ft., From ..... ft. to ..... ft.

From ..... ft. to ..... ft., From ..... ft. to ..... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .....

Grout Intervals: From ..... 4' ft. to ..... 14' ft., From ..... ft. to ..... ft., From ..... ft. to ..... ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
POND

Direction from well?

N WHow many feet? 100 ft.

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0'	<u>18'</u>	<u>TOP SOIL</u>			
<u>18'</u>	<u>40'</u>	<u>SAND</u>			
<u>40'</u>	<u>50'</u>	<u>GRAVEL</u>			











































