


LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <i>Butler</i>	<i>NE 1/4 SE 1/4 NW 1/4</i>	<i>8</i>	<i>T 26 S</i>	<i>R 4 E</i>

Distance and direction from nearest town or city street address of well if located within city?

*2 1/2 miles west of Towanda*WATER WELL OWNER: *Ed Edson Towanda Kansas*RR#, St. Address, Box #: *401 N. 10th* 69144
City, State, ZIP CodeBoard of Agriculture, Division of Water Resources
Application Number:LOCATE WELL'S LOCATION WITH
AN "X" IN SECTION BOX:4 DEPTH OF COMPLETED WELL *115* ft. ELEVATION:Depth(s) Groundwater Encountered 1. *75* ft. 2. ft. 3. ft.WELL'S STATIC WATER LEVEL *50* ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield *50* gpm: Well water was ft. after hours pumping gpmBore Hole Diameter *8 1/2* in. to ft., and in. to ft.

WELL-WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)
2 PVC 4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued Clamped Welded Threaded Blank casing diameter *5* in. to *115* ft. Dia in. to ft., Dia in. to ft.Casing height above land surface *18* in., weight *200* lbs./ft. Wall thickness or gauge No. *214*

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel
2 Brass 4 Galvanized steel

5 Fiberglass

6 Concrete tile

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

7 PVC

8 RMP (SR)

9 ABS

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot
2 Louvered shutter 4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 RMP (SR)

9 ABS

SCREEN-PERFORATED INTERVALS: From *50* ft. to *115* ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From *40* ft. to *115* ft., From ft. to ft.

From ft. to ft., From ft. to ft.

] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 OtherGrout Intervals: From *2* ft. to *12* ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines
2 Sewer lines 5 Cess pool
3 Watertight sewer lines 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well

16 Other (specify below)

Direction from well? *5* How many feet? *75*

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

*0 3 Soil**2 14 Clay**25 25 Rock**60 85 Shale**85 115 Lime**85 115 Shale*CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) *5/12/82* and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. *251* This Water Well Record was completed on (mo/day/yr) *6/29/82*under the business name of *Winter Well Drilling* by (signature) *Charles Winter*

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.