


1 LOCATION OF WATER WELL:	Fraction County: Butler	NW 1/4 NW 1/4 NW 1/4	Section Number 19	Township Number T 26 S S	Range Number R 4E E/W	
Distance and direction from nearest town or city street address of well if located within city?						
1 mile So. of Santa Fe Lake Rd. & 254 Hwy., 1/4 W., 1/8 S.			Augusta, Kansas			
2 WATER WELL OWNER:	Eastman, Larry		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #	3216 N. Salina		Application Number:			
City, State, ZIP Code	Wichita, Kansas					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL	112 ft. ELEVATION:		
			Depth(s) Groundwater Encountered	1 ft. 2 ft. 3 ft.	ft.	
			WELL'S STATIC WATER LEVEL	65 ft. below land surface measured on mo/day/yr	2-2891	
			Pump test data: Well water was	ft. after hours pumping	gpm	
			Est. Yield gpm: Well water was	ft. after hours pumping	gpm	
			Bore Hole Diameter 11 in. to 112 ft. and	in. to ft.		
			WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well		
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering	12 Other (Specify below)		
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
			Was a chemical/bacteriological sample submitted to Department? Yes No X	Water Well Disinfected? Yes X No		
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below) SDR-26	CASING JOINTS: Glued X Clamped Welded Threaded	
Blank casing diameter	5 in. to 62 ft.	in. to 62 ft., Dia	in. to ft., Dia	in. to ft.		
Casing height above land surface	12 in.	weight 2.29 lbs./ft.	Wall thickness or gauge No. 214			
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATED INTERVALS:	From 62 ft.	to 112 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 24 ft.	to 112 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:	From 4 ft.	to 24 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) None Apparent	
Direction from well?	How many feet?					
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	3	topsoil				
3	5	clay				
5	70	brown shale				
70	112	grey shale				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-28-91					and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 236	This Water Well Record was completed on (mo/day/yr) 5-1-91					
under the business name of Harp Well and Pump Service, Inc.	by (signature) <i>Mary Arnold</i>					