

1 LOCATION OF WATER WELL		Fraction County: Butler 015 NE $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number Distance and direction from nearest town or city street address of well if located within city?	Township Number T 26 S	Range Number R 4 E			
2 WATER WELL OWNER:		Don Cook R.R. Box 88CC Towanda Kans 67144						
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources						
City, State, ZIP Code :		Application Number:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 145 ft. ELEVATION: 90 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 75 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 200 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8.5 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No						
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued X Clamped Welded Threaded				
Blank casing diameter		5 in. to 60 ft. Dia	in. to ft. Dia	in. to ft.				
Casing height above land surface		15 in., weight 200	lbs./ft. Wall thickness or gauge No. 12.14					
TYPE OF SCREEN OR PERFORATION MATERIAL:		5 Gauzed wrapped 1 Continuous slot 2 Louvered shutter	7 PVC 6 Wire wrapped 8 RMP (SR) 4 Key punched	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	11 None (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Fiberglass 6 Concrete tile	7 Torch cut					
SCREEN-PERFORATED INTERVALS:		From 60 ft. to 110 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.			
GRAVEL PACK INTERVALS:		From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 3 ft. to 13 ft.	2 Cement grout From ft. to ft.	3 Bentonite ft. to ft.	4 Other ft. to ft.			
What is the nearest source of possible contamination:		1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage			
Direction from well?		N How many feet? 100						
FROM		TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
3	3	Soil						
3	15	Clay						
15	25	Rock						
25	35	Shale						
35	125	Lime						
125	145	Shale						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 11 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-21-85		and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 215		This Water Well Record was completed on (mo/day/yr) 3-22-85						
under the business name of Winter Well Drilling		by (signature) Charles Winter						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.								