

LOCATION OF WATER WELL:

Fraction

SW  $\frac{1}{4}$  SW  $\frac{1}{4}$  NW  $\frac{1}{4}$ 

Section Number

30

Township Number

T 26 S

Range Number

R 4 EW

Distance and direction from nearest town or city street address of well if located within city?


LOT 7, S From Santa Fe Lake Rd & 21<sup>st</sup> 2 1/2 N. E. sideWATER WELL OWNER: Buck BannonRR#, St. Address, Box #: #3 MulberryCity, State, ZIP Code: Towanda, KS

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N



4 DEPTH OF COMPLETED WELL 100 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 40 ft. 2. 70 ft. 3. ft.

WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 20 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes Yes; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)  
2 PVC 4 ABS5 Wrought iron  
6 Asbestos-Cement  
7 Fiberglass8 Concrete tile  
9 Other (specify below)

CASING JOINTS: Glued Clamped

Welded

Threaded

ft.

Blank casing diameter 5 in. to ft., Dia in. to ft., Dia in. to in. to ft.

Casing height above land surface 12 in., weight 200 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel  
2 Brass 4 Galvanized steel5 Fiberglass  
6 Concrete tile7 PVC  
8 RMP (SR)  
9 ABS

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot  
2 Louvered shutter 4 Key punched5 Gauzed wrapped  
6 Wire wrapped  
7 Torch cut

8 Saw cut

11 None (open hole)

9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 60 ft. to 100 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 100 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines  
2 Sewer lines 5 Cess pool  
3 Watertight sewer lines 6 Seepage pit  
7 Pit privy  
8 Sewage lagoon  
9 Feedyard

10 Livestock pens

14 Abandoned water well

11 Fuel storage

15 Oil well/Gas well

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	6	Earth			
6	8	Gravel (Red)			
8	22	Brown clay (light)			
22	35	Yellow clay			
35	78	Grey shaly line			
78	100	Dark grey shale			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/19/88 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/year) 8/25/88

under the business name of Reiserer Well Drilling by (signature) Jerry J. Reiserer

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top

three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.