


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Butler	Fraction NW 1/4 NW 1/4 SW 1/4	Section Number 28	Township Number T 26 S	Range Number R 5 EW
Distance and direction from nearest town or city street address of well if located within city? APPROX 4 1/2 mi. South of El Dorado, KS.				
2 WATER WELL OWNER: RR#, St. Address, Box # : 205 W. Central	Board of Agriculture, Division of Water Resources Application Number:			
City, State, ZIP Code : El Dorado, KS. 67042				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N  W E S	4 DEPTH OF COMPLETED WELL 23.5 ft. ELEVATION: 10 ft. 2. 3.5 ft. 3. ft. Depth(s) Groundwater Encountered 1. 10 ft. 2. 3.5 ft. 3. ft. WELL'S STATIC WATER LEVEL 3.5 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm ; Well water was ft. after hours pumping gpm Bore Hole Diameter 3 1/4 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Thermometer 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes X No ✓ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No ✓				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued ✓ Clamped ✓ Welded ✓ Threaded ✓		
Blank casing diameter 2 in. to 13.5 ft. Dia in. to ft. Dia in. to ft.	lbs./ft. Wall thickness or gauge No. 1.8			
Casing height above land surface 1.8 in., weight ft.				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 0.0				
SCREEN-PERFORATED INTERVALS: From 23.5 ft. to 13.5 ft. From ft. to ft. From ft. to ft.				
GRAVEL PACK INTERVALS: From 23.5 ft. to 11.5 ft. From ft. to ft. From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 11.5 ft. to 9.5 ft., From ft. to ft. From ft. to ft. From ft. to ft.	10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage LANDFILL			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 2 Sewer lines 5 Cess pool 8 Sewage lagoon 3 Watertight sewer lines 6 Seepage pit 9 Feedyard How many feet?				
FROM 0 TO 14 LITHOLOGIC LOG BRN CLAY 21 23.5 BRN SILT 21 23.5 TAN L.S	FROM 0 TO 14 PLUGGING INTERVALS			
P 9				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 7-10-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 569 This Water Well Record was completed on (mo/day/yr) 7-10-95 by (signature) David Swingle under the business name of Max's Enterprises
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.