


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction County: Butler	Section Number 28	Township Number T 26 S	Range Number R 5 EW	
Distance and direction from nearest town or city street, address of well if located within city? APPROX. 4 1/2 mi. South of El Dorado, KS.					
2 WATER WELL OWNER:	Butler County, 205 W. Central, El Dorado, KS. 67042				Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL 28 ft. ELEVATION: 14 1/2 ft. ft. ft. ft.
	Depth(s) Groundwater Encountered 1. 14 1/2 ft. below land surface measured on mo/day/yr				
	WELL'S STATIC WATER LEVEL 14 1/2 ft. below land surface measured on mo/day/yr				
	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft.				
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) 120 meters				
	Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted				Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input checked="" type="checkbox"/>
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC 3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/> Welded <input type="checkbox"/> Threaded <input type="checkbox"/>	
Blank casing diameter	2 in. to 18 ft.	Dia in. to ft., Dia in. to ft.			
Casing height above land surface	1.8 in.	weight lbs./ft.	Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole) 0.0	
SCREEN-PERFORATED INTERVALS:	From 28 ft. to 18 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 28 ft. to 16 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
6 GROUT MATERIAL:	1 Neat cement 2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:	From 16 ft. to 13 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Landfill	
Direction from well?	How many feet? 10				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	18	BRN Clay			
13	27.5	BRN Silt			
27.5	28	L.S. - Cherr			
P/10					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **7-7-95** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **548** This Water Well Record was completed on (mo/day/year) **7-7-95** by (signature) **David Hough** under the business name of **Max's Enterprises**