


1 LOCATION OF WATER WELL: County: Butler Fraction: NW 1/4 SE 1/4 NW 1/4 Section Number: 28 Township Number: T 26 S Range Number: R 5 E/W

Distance and direction from nearest town or city street address of well if located within city?

Approx 4 1/2 MI. South of Eldorado, Ks.

2 WATER WELL OWNER: Butler County Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 205 W. Central Application Number:
City, State, ZIP Code: Eldorado, Ks. 67024

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 18' ft. ELEVATION: 15' ft.
Depth(s) Groundwater Encountered 1. 15' ft. 2. 15' ft. 3. 15' ft.
WELL'S STATIC WATER LEVEL 15' ft. below land surface measured on mo/day/yr
Pump test data: Well water was 15' ft. after 15' hours pumping 15' gpm
Est. Yield 15' gpm: Well water was 15' ft. after 15' hours pumping 15' gpm
Bore Hole Diameter: 8 1/4 in. to 8 1/4 in. ft., and 8 1/4 in. to 8 1/4 in. ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Piezometer
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted 15'
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
Blank casing diameter 2 in. to 2 in. Dia. 2 in. to 2 in. Dia. 2 in. to 2 in. Dia. 2 in. to 2 in. Dia.
Casing height above land surface 1.8 in. weight 1.8 lbs./ft. Wall thickness or gauge No. 1.8
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 1.8
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 1.8
SCREEN-PERFORATED INTERVALS: From 18' ft. to 8' ft. From 18' ft. to 8' ft. From 18' ft. to 8' ft. From 18' ft. to 8' ft.
GRAVEL PACK INTERVALS: From 18' ft. to 8' ft. From 18' ft. to 8' ft. From 18' ft. to 8' ft. From 18' ft. to 8' ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 1.8
Grout Intervals: From 18' ft. to 8' ft. From 18' ft. to 8' ft. From 18' ft. to 8' ft. From 18' ft. to 8' ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) LANDFILL
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>14</u>	<u>RED BRN CLAY</u>			
<u>14</u>	<u>18</u>	<u>SILTY W CLAY + L.S. FRAG</u>			
<u>18</u>		<u>h.s.</u>			
		<u>2.4</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-8-95 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 568 This Water Well Record was completed on (mo/day/yr) 7-8-95
under the business name of Max's Enterprises by (signature) David Hargrave