

P-1D 231033

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County: Butler	Section Number NW $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$	Township Number T 26 S	Range Number R 5 E/W		
Distance and direction from nearest town or city street address of well if located within city? 4 miles S & 1 mile W of Eldorado @ Butler Co. Landfill							
2 WATER WELL OWNER:		Butler County 1st Floor, Court House, 205 W Central Eldorado KS 67042		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 94.3 ft. ELEVATION: Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 83 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:		1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Threaded Flush			
Blank casing diameter		2 in. to ft.	Dia in. to ft.	Dia in. to ft.			
Casing height above land surface		24 in., weight 703		lbs./ft. Wall thickness or gauge No. Sch 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel		5 Fiberglass 8 RMP (SR) 6 Concrete tile 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)							
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched							
SCREEN-PERFORATED INTERVALS: From 83.9 ft. to 93.9 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 81.6 ft. to 94.3 ft., From ft. to ft. From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0.0 ft. to 3.0 ft., From 3.0 ft. to 78.1 ft., From 78.1 ft. to 81.6 ft.							
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (Specify below) Landfill							
Direction from well? N How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0.0	10.0	Clay					
10.0	88.9	Limestone					
88.9	89.8	Shale					
89.8	93.4	Limestone					
93.4	94.3	Shale w/limestone stringers					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 8-3-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 8-31-95							
under the business name of GSI							
by (signature) Allison Juras							