

Butler Co

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL:		Fraction County: Butler	SW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 21	Township Number T 26 S	Range Number R 5 E	
Distance and direction from nearest town or city street address of well if located within city? 5 mi. south of El Dorado							
2 WATER WELL OWNER:		Butler County Landfill RR#, St. Address, Box # : 2963 SW 40th St. City, State, ZIP Code : El Dorado, KS 67042		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 16 ft. ELEVATION: Depth(s) Groundwater Encountered 1 8.51 Tds ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 5.7 ft. below land surface measured on mo/day/yr 8/19/04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well p120 (PZ-7)					
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 2 PVC	6 Asbestos-Cement 3 RMP (SR) 4 ABS	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded X		
Blank casing diameter 2 in. to 6 ft., Dia in. to ft., Dia in. to ft.							
Casing height above land surface 34 in., weight lbs./ft. Wall thickness or guage No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 5 Fiberglass 6 Concrete tile	10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		5 Guazed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify) ft.	11 None (open hole)			
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched					
SCREEN-PERFORATED INTERVALS: From 6 ft. to 16 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 4 ft. to 16 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement		2 Cement grout	3 Bentonite	4 Other ft. to ft., From ft. to ft.			
Grout Intervals: From 4 ft. to 0 ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage					14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit					
Direction from well?		How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
0'	1'	Organic material	0'	4'	Bentonite grout		
1'	11.5'	Clay, gray, dry, stiff					
11.5'	16'	Clay/limestone mix, soft, plastic					
RECEIVED							
SEP 24 2004							
BUREAU OF WATER							

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-18-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 704 This Water Well Record was completed on (mo/day/yr) 8-18-04	
under the business name of Max's by (signature) David Hargan	

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.