


new 7

1 LOCATION OF WATER WELL:	Fraction County: Butler	SE $\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$	Section Number 2	T 26 S	R 5 E	Range Number W
Distance and direction from nearest town or city street address of well if located within city?						
City of Eldorado, 1st & Griffin, Eldorado, KS.						
2 WATER WELL OWNER:	City of Eldorado			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #:	213 E. 1st.			Application Number:		
City, State, ZIP Code:	Eldorado, Ks.					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL: 14' ft. ELEVATION: 8' ft. Depth(s) Groundwater Encountered 1. 8' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 4.5 ft. below land surface measured on mo/day/yr 7-1-98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2 in. to 14 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No		
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped	
Blank casing diameter	2.375 in. to 4'	ft. Dia.	in. to ft. Dia.	in. to ft.	Welded Threaded	X SDR 13 SCH 40
Casing height above land surface	Flush Mt.	in., weight	lbs./ft. Wall thickness or gauge No.	in. to ft.		
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATED INTERVALS:	From 14'	ft. to 4'	ft. to 4'	ft. to ft.	ft. to ft.	
GRAVEL PACK INTERVALS:	From 14'	ft. to 3'	ft. to 3'	ft. to ft.	ft. to ft.	
6 GROUT MATERIAL:	1 Neat cement Grout Intervals: From 3' ft. to 2 1/2' ft.	2 Cement grout From 2 1/2' ft. to 0' ft.	3 Bentonite 0' ft. to 0' ft.	4 Other		
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage FOUREL 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well?	South					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2	Grass-dk brn silty clay topsoil, damp, no odor, firm, low plast.				
2	12	Red brn clay, firm to stiff, med plasticity, moist, no odor.				
12	14	Yellow brn gravelly clay, highly plastic, moist to wet, no odor, ls rx chert gravel.				
F1. Mt. OK'd by Don Taylor						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was						

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-23-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 8-13-98

INSTRUCTIONS: Use typewriter or ball point pen. **PLEASE PRESS FIRMLY** and **PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.