


۷۸۹

1 LOCATION OF WATER WELL:		Fraction NE $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$		Section Number 2	Township Number T 26 S	Range Number R 5 EW
Distance and direction from nearest town or city street address of well if located within city? 1st & Main street, ElDorado, KS.						
2 WATER WELL OWNER:		Nations Bank 200 N. Main ElDorado, KS.		Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:				4 DEPTH OF COMPLETED WELL 15' ft. ELEVATION: Depth(s) Groundwater Encountered 15' ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 7.1 ft. below land surface measured on mo/day/yr 7-2-98 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm, Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2 in. to 15' ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		
5 TYPE OF BLANK CASING USED:		1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded <input checked="" type="checkbox"/> SDR 13 in. to ft.
Blank casing diameter 2.375 in. to 5' ft., Dia in. to ft., Dia in. to ft. Wall thickness or gauge No. SCH 40						
Casing height above land surface FLUSH MT. in. weight lbs./ft. Wall thickness or gauge No. SCH 40						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)		
SCREEN-PERFORATED INTERVALS: From 15' ft. to 5' ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 15' ft. to 4' ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 4' ft. to 3' ft., From 3' ft. to 0' ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage <input checked="" type="checkbox"/> FARM 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)		
Direction from well? North						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-23-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/year) 8-13-98 under the business name Q.B. Environmental Drilling by (signature) James Biles						

INSTRUCTIONS: Use typewriter or ball point pen. **PLEASE PRESS FIRMLY** and **PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to **WATER WELL OWNER** and retain one for your records.