WATER WELL RECORD	Form WWC-5	Division of Wate	r Resources App. N	o.	
1 LOCATION OF WATER WELL: County: Butler	Fraction NE 1/4 NE 1/4 SE 1/4 SE 1/4	Section Number		Range Number R 5	
Street/Rural Address of Well Location; if unknown, distance & direction Global Positioning System (GPS) inform					
from nearest town or intersection: If a			(in decimal degrees)		
2395 SW Boyer Rd., El Dorado, K	Longitude: (in decimal degrees)				
2393 SW Boyer Ru., El Dorado, RS		Elevation:			
		<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
2 WATER WELL OWNER: Shell Oil Products		Collection Method:			
RR#, Street Address, Box #: P.O. Box 1087		GPS unit (Make/Model:)			
City, State, ZIP Code : Huffman, TX 77336		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
		Est. Accuracy:	3 m, 🔲 3-5 m, 🗀] 5-15 m, □ >15 m	
3 LOCATE WELL					
	4 DEPTH OF COMPLETED WELL .8'				
SECTION BOX: Depth(s) Groun	ndwater Encountered (1).7	π. (2)π. (3)π.			
		. below land surface measured on mo/day/yr			
		ft. after hours pumping gpm			
		er was hours pumping			
W E Bore Hole Dia	fore Hole Diameter 8in. to .8ft., andin. toft.				
WELL WATE	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well				
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No					
S If yes, mo/day/yr sample was submitted.					
mile Water well disinfected? ☐ Yes ☑ No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: Glued Clamped Welded Threaded					
Casing diameter .2 in. to					
Casing height above land surface. Flush in., Weight :					
TYPE OF SCREEN OR PERFORATION			oniness of Baage !		
Steel Stainless Steel PVC Other (Specify)					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)					
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)					
SCREEN-PERFORATED INTERVALS: From					
From					
GRAVEL PACK INTERVALS: From .8'					
From					
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Coacce Grout Intervals: From 3' ft. to 2' ft., From ft. to 7' ft., From ft. to 7' ft., From ft.					
Grout Intervals: From 3' ft. to 2' ft., From ft. to 7' ft., From ft., From ft. to ft., From ft.					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)					
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well					
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well Direction from well					
Direction from well				TOOLS OF THE PARTY OF	
FROM TO LITHOLO	GIC LOG FROM	TO LITHO. L	OG (cont.) or PLU	JGGING INTERVALS	
0 8' silty clay, firm, damp					
8' limestone					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .3/12/09 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 7.10 This Water Well Record was completed on (mg/day/year) .3/16/09					
under the business name of Below Ground Surface. Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies					
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html.					
KSA 82a-1212		Check: \coprod W	hite Copy, 🔲 Bi	lue Copy, 🔲 Pink Copy	