

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Butler		Fraction NW ¼ NW ¼ SE ¼		Section Number 4		Township Number T 26 S		Range Number R 5 E			
Distance and direction from nearest town or city street address of well if located within city? 107 Hogoboom Dr. El Dorado, Kansas				Global Positioning System (decimal degrees, min. of 4 digits) Latitude: N 37.81715° Longitude: W 96.88811° Elevation: RIM: 1323.43 TOC: 1323.04 Datum: above mean sea level Data Collection Method: legal survey							
2 WATER WELL OWNER: KDHE-BER RR#, St. Address, Box # : 1000 SW Jackson City, State, ZIP Code : Topeka, Kansas 66612				3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>							
4 DEPTH OF COMPLETED WELL 13 ft. Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 6.82 ft. below land surface measured on mo/day/yr 4/22/09 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm: Well water was _____ ft. after _____ hours pumping _____ gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well				Was a chemical/bacteriological sample submitted to Department? Yes _____ No X ; If yes, mo/day/yr _____ Sample was submitted _____ Water Well Disinfected? Yes _____ No X							
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 3 ft., Dia _____ in. to _____ ft., Dia _____ in. to _____ ft. Casing height below land surface 0.39 ft., Weight _____ lbs./ft. Wall thickness or gauge No. _____				CASING JOINTS: Glued _____ Clamped _____ Welded _____ Threaded X							
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)				SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) _____							
SCREEN-PERFORATED INTERVALS: From 3 ft. to 13 ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft.				GRAVEL PACK INTERVALS: From 2 ft. to 13 ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1 ft. Grout Intervals From 1 ft. to 2 ft. From _____ ft. to _____ ft. From _____ ft. to _____ ft.				What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well Direction from well? E How many feet? ~185							
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		4		Silty clay, brown, with limestone gravel							
				limestone seam at 0.5-1.5 feet							
4		13		Limestone, yellow brown							
</											