


1 LOCATION OF WATER WELL:	Fraction County: Butler	SE $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$	Section Number 1	Township Number T 26 S	Range Number R 5 CEW		
Distance and direction from nearest town or city street address of well if located within city? SE of El Dorado							
2 WATER WELL OWNER:	City of El Dorado, KS RR#, St. Address, Box # : 220 East First Street		Board of Agriculture, Division of Water Resources Application Number:				
City, State, ZIP Code :	El Dorado, KS 67042						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 9.3 ft. ELEVATION: Surface 1265.4 Depth(s) Groundwater Encountered 1. 7.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 7 ft. below land surface measured on mo/day/yr 8-14-85 Pump test data: Well water was N/A ft. after hours pumping gpm Est. Yield N/A. gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 9.5 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted				
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Clamped Welded Threaded X		
Blank casing diameter	4	in. to	3.8	ft., Dia	in. to ft., Dia in. to ft.		
Casing height above land surface	30	in., weight			lbs./ft. Wall thickness or gauge No. 40		
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)			
SCREEN-PERFORATED INTERVALS:	From. 3.8	ft. to 9.3	ft., From ft. to ft.				
GRAVEL PACK INTERVALS:	From. 3.8	ft. to 9.5	ft., From ft. to ft.				
6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite	4 Other					
Grout Intervals:	From. 0	ft. to 1.5	ft., From. 1.5	ft. to 3.5	ft., From ft. to ft.		
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Landfill 30		
Direction from well?	W	How many feet?					
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	1	Silty Clay					
1	3	Gravel With Silty Clay					
3	4.5	Silty Clay					
4.5	6	Gravel With Silty Clay					
6	9.5	Silty Clay, Trace Gravel					
9.5	-	Apparent Limestone					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-6-85					and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 416	This Water Well Record was completed on (mo/day/yr) 10-25-85					under the business name of TERRACON CONSULTANTS INC by (signature) <i>John S. Sauer</i>	
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							