

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: BUTLER	SE $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$	2	T 26 S	R 5 E

Distance and direction from nearest town or city street address of well if located within city?

147' E. AND 52' S. of the center of Olive and Main

2 WATER WELL OWNER: LEWIS AND WEST	MWI
RR#, St. Address, Box # : 400 S. Main	Board of Agriculture, Division of Water Resources
City, State, ZIP Code : EL DORADO, KS	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 25.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 15.0 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 14.5 ft. below land surface measured on mo/day/yr 12/10/92
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter in. to ft. and in. to ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded	
2 PVC 4 ABS 7 Fiberglass Threaded	
Blank casing diameter 2 in. to ft. Dia in. to ft. Dia in. to ft.	
Casing height above land surface Flush in., weight lbs./ft. Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 15.5 ft. to 24.5 ft. From ft. to ft.	
GRAVEL PACK INTERVALS: From 13.5 ft. to 25.5 ft. From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
GROUT INTERVALS: From 0 ft. to 11.5 ft. From 11.5 ft. to 13.5 ft. From ft. to ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage EXCAVATED USTS	
Direction from well?	How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Concrete			
5	2.0	Clay, DARK BROWN			
2.0	10	CLAY, BROWN			
10	22	CLAY, BROWN, SILTY			
22	25.5	CLAY, GRAVEL, SILT			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/30/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) under the business name of by (signature) Charles Harper
--