

LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 NE 1/4 S 5 Section Number Township Number Range Number
County: BUTLER Township: T 26 S Range: R 5 E E/W
Distance and direction from nearest town or city street address of well if located within city?


EL DORADO KANSAS 1 W 3/4 N
TER WELL OWNER: SDS INC

Board of Agriculture, Division of Water Resources
Application Number:

RR#, St. Address, Box #: RI EL DORADO KS

City, State, ZIP Code

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 52' ft. ELEVATION: 50' ft.

Depth(s) Groundwater Encountered: 1. 50' ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 31' ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 10 gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter: 9' in. to 52' ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile Casing JOINTS: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter: 6" in. to 42' ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface: 3' in., weight lbs./ft. Wall thickness or gauge No.

7 PVC 10 Asbestos-cement

TYPE OF SCREEN OR PERFORATION MATERIAL: 11 Other (specify)

1 Steel 3 Stainless steel 8 RMP (SR) 12 None used (open hole)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS

5 Gauzed wrapped 8 Saw cut 11 None (open hole)

6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 42' ft. to 52' ft., From ft. to ft., From ft. to ft.

From 42' ft. to 52' ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 42' ft. to 52' ft., From ft. to ft., From ft. to ft.

From 42' ft. to 52' ft., From ft. to ft., From ft. to ft.

1 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 42' ft. to 52' ft., From 42' ft. to 52' ft., From 17 1/2 ft. to 34 1/2 ft., From 17 1/2 ft. to 34 1/2 ft.

10 Livestock pens 14 Abandoned water well

11 Fuel storage 15 Oil well/Gas well SE

12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

How many feet?

Direction from well? FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 4 4 32 SHALE

0 4 4 32 LIME STONE

0 4 4 32 LIME STONE