


1 LOCATION OF WATER WELL: County: Bulter Fraction: NE 1/4 SE 1/4 SE 1/4 Section Number: 7 Township Number: T 26 S Range Number: R 5 E

Distance and direction from nearest town or city street address of well if located within city?

from Kechur-Towanda Rd. & Haverhill Rd. 2 West + 1/3 N. W. Side Rd.

2 WATER WELL OWNER: Rocky Casper  
RR#, St. Address, Box #: Rt 1 Box 1728  
City, State, ZIP Code: EL DORADO KS 67042  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 84 ft. ELEVATION: 60 ft.

Depth(s) Groundwater Encountered: 1 46 ft. 2. 60 ft. 3. Oct 31 88

WELL'S STATIC WATER LEVEL: 40 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 15 gpm. Well water was 10 ft. after 15 hours pumping 15 gpm

Est. Yield: 15 gpm. Well water was 10 ft. after 15 hours pumping 15 gpm

Bore Hole Diameter: 10 in. to 10 ft., and 10 in. to 10 ft.

WELL WATER TO BE USED AS:

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes Yes No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter: 5 in. to 5 ft., Dia. 5 in. to 5 ft., Dia. 5 in. to 5 ft.

Casing height above land surface: +12 in., weight 200 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

SCREEN-PERFORATED INTERVALS: From 64 ft. to 84 ft. From 64 ft. to 84 ft.

GRAVEL PACK INTERVALS: From 20 ft. to 84 ft. From 20 ft. to 84 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 20 ft. From 3 ft. to 20 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? DOWN SLOPE How many feet? +50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	earth			
2	6	green shale			
6	40	gray shale			
40	54	gray shale			
		line water			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Oct 31 88 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 493 This Water Well Record was completed on (mo/day/yr) NOV 29 88

under the business name of Reisner Well Drilling by (signature) Jerry Reisner