


1 LOCATION OF WATER WELL:	Fraction County: <b>BUTLER</b>	Section Number 10	Township Number T 26 S	Range Number R 50 E/W			
Distance and direction from nearest town or city street address of well if located within city? <b>TEXACO REFINERY</b>							
2 WATER WELL OWNER:	TEXACO						
RR#, St. Address, Box #:	PO BOX 1121 EL DORADO KS						
City, State, ZIP Code							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
4 DEPTH OF COMPLETED WELL:	20 ft. ELEVATION:						
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. ft.							
WELL'S STATIC WATER LEVEL 999 ft. below land surface measured on mo/day/yr							
Pump test data: Well water was ft. after hours pumping gpm							
Est. Yield gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter 10 in. to 20 ft. and in. to ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)			
Casing joints: Glued Clamped Welded Threaded							
Blank casing diameter	2 in. to 5	ft. Dia	in. to ft. Dia	in. to ft.			
Casing height above land surface	24 in.	weight	lbs./ft.	Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)			
SCREEN-PERFORATED INTERVALS: From 5 ft. to 20 ft. From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 3 ft. to 20 ft. From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals: From 0 ft. to 3 ft. From ft. to ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) <b>REFINERY</b>			
Direction from well? <b>WITHIN</b> How many feet?							
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS	
0	TD	<b>SILTY CLAY</b>					
<b>WYSHALE + LIME STONE</b>							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>8/30/93</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>102</b> This Water Well Record was completed on (mo/day/year) <b>8/30/93</b> by (signature) <b>John GAYNE INC</b>							