

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction County: Butler	Section Number T 26 S	Township Number R 5 E	Range Number	
Distance and direction from nearest town or city street address of well if located within city? TEXACO REFINERY MW 169					
2 WATER WELL OWNER:	TEXACO				
RR#, St. Address, Box #	PO BOX 1121 EL DORADO KS				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					
4 DEPTH OF COMPLETED WELL... 28 ft. ELEVATION:					
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
WELL'S STATIC WATER LEVEL 79 ft. below land surface measured on mo/day/yr					
Pump test data: Well water was ft. after hours pumping gpm					
Est. Yield gpm: Well water was ft. after hours pumping gpm					
Bore Hole Diameter 10 in. to 28 ft., and in. to ft.					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>					
5 TYPE OF BLANK CASING USED:	1 Steel 2 PVC	3 RMP (SR)	5 Wrought iron	8 Concrete tile	
		4 ABS	6 Asbestos-Cement	9 Other (specify below)	
			7 Fiberglass	Welded Threaded	
Blank casing diameter	4	in. to 8	ft., Dia	in. to ft., Dia in. to ft.	
Casing height above land surface	24	in., weight	lbs./ft. Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	12 None used (open hole)	
SCREEN-PERFORATED INTERVALS: From 8 ft. to 28 ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 6 ft. to 28 ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals:	From 0 ft. to 6 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.	
What is the nearest source of possible contamination:					
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
Direction from well? WITHIN How many feet? WITHIN					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	TD	SILTY CLAY W			
SALT + LIME STONE					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/30/93 and this record is true to the best of my knowledge and belief. Kansas				
Water Well Contractor's License No. 102	This Water Well Record was completed on (mo/day/yr) 8/30/93 by (signature) B. M. LAYNE				