

1 LOCATION OF WATER WELL:		Fraction Ne 1/4 Ne 1/4 Ne 1/4	Section Number 15	Township Number T 26 S	Range Number R 5 EW		
Distance and direction from nearest town or city street address of well if located within city? 1/2 Mile S. of El Dorado, Kansas							
2 WATER WELL OWNER:		Getty Refining & Marketing Co.		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		1401 South Douglas Road		Application Number:			
City, State, ZIP Code :		El Dorado, Kansas 67042					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 31.2 ft. ELEVATION: 1238.8 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 13.1 ft. below land surface measured on mo/day/yr 3/17/81 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to Total depth ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X Water Well Disinfected? Yes No X					
5 TYPE OF BLANK CASING USED:		5 Wrought iron 1 Steel 3 RMP (SR) 2 PVC 4 ABS	8 Concrete tile 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued Clamped Welded Yes Threaded			
Blank casing diameter		4 in. to ft.	Dia in. to ft.	Dia in. to ft.			
Casing height above land surface		45.6 in.	weight 10.8	lbs./ft.	Wall thickness or gauge No. 14		
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 1 Steel 3 Stainless steel 2 Brass 4 Galvanized steel	10 Asbestos-cement 8 RMP (SR) 6 Concrete tile	11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched	8 Saw cut 6 Wire wrapped 7 Torch cut	11 None (open hole) 9 Drilled holes 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 17.2 ft. to 31.2 ft.	From ft. to ft.	From ft. to ft.			
GRAVEL PACK INTERVALS:		From 10.0 ft. to 31.2 ft.	From ft. to ft.	From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement Grout Intervals: From 0.0 ft. to 10.0 ft., From ft. to ft., From ft. to ft.	2 Cement grout 3 Bentonite	4 Other	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage		
What is the nearest source of possible contamination:		7 Pit privy 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)				
Direction from well? Northwest		How many feet? 60'					
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0.0	0.2	Gravel					
0.2	1.2	Dark brown silty clay, moist, stiff					
1.2	29.8	Brown silty clay, moist, stiff					
29.8	31.2	Brown silty clay w/trace rock					
31.2		Bedrock					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:		This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/17/81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102. This Water Well Record was completed on (mo/day/yr) 6-9-81 under the business name of LAYNE-WESTERN CO. INC by (signature) Diana S. Bennington					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							