

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction 1/4 NW 1/4 NW 1/4	Section Number 28	Township Number T 26 S	Range Number R 5 E		
Distance and direction from nearest town or city street address of well if located within city? 5 MILES SOUTH OF EL DORADO						
2 WATER WELL OWNER:	BUTLER COUNTY LANDFILL COUNTY ENGINEER, BUTLER CO. COURTHOUSE EL DORADO, KANSAS 67042		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 22 ft. ELEVATION: 1279.40 TOC Depth(s) Groundwater Encountered 1 17 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 11-2-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 in. to 22 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No					
5 TYPE OF BLANK CASING USED:	1 Steel <input checked="" type="checkbox"/> PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	CASING JOINTS: Glued Clamped Welded <input checked="" type="checkbox"/> Threaded		
Blank casing diameter	2	in. to 12	ft., Dia	in. to ft., Dia in. to ft.		
Casing height above land surface	24	in., weight	lbs./ft. Wall thickness or gauge No. SCHEDULE 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot 2 Louvered shutter	2 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)		
SCREEN-PERFORATED INTERVALS:	From 12	ft. to 22	ft., From ft. to ft.			
GRAVEL PACK INTERVALS:	From 9-5	ft. to 22	ft., From ft. to ft.			
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:	From 0	ft. to 9-5	ft., From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:	1 Septic tank 2 Sewer lines 3 Watertight sewer lines	4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage		
Direction from well?	How many feet?					
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
0	8	FAT CLAY, DARK REDDISH BROWN, MOIST, STIFF				
8	9	GRAVELLY CLAY, REDDISH BROWN, VERY MOIST, STIFF				
9	18	SHALE, LIGHT GRAY AND LIGHT BROWN, CALCAREOUS, HARD				
18	22	LIMESTONE, TAN, HARD, WITH ALTERNATING INTERBEDDED SHALE SEAMS				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **10-31-93** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **524** This Water Well Record was completed on (mo/day/yr) **1-3-94** under the business name of **ALLIED ENVIRONMENTAL CONSULTANTS** by (signature) **William H. Keltner President**

INSTRUCTIONS: Use typewriter or ball point pen. **PLEASE PRESS FIRMLY** and **PRINT** clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.