

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number			
County: Butler	NE $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$	29	T 26 S	R 50 E			
Distance and direction from nearest town or city street address of well if located within city? 6 N - 4 E of Augusta							
2 WATER WELL OWNER:	Jim Fanning Eldorado Kan		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box #	RR 1 Box 117A		Application Number: 67042				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
4 DEPTH OF COMPLETED WELL. 145 ft. ELEVATION: ft. 3.							
Depth(s) Groundwater Encountered 1. 90 ft. 2. ft. 3. ft.							
WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr							
Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15 gpm. Well water was ft. after hours pumping gpm							
Bore Hole Diameter 8.5 in. to ft., and in. to ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil-field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well							
Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped				
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded				
2 PVC	7 Fiberglass		Threaded				
Blank casing diameter 5 in. to 60 ft., Dia. in. to ft., Dia. in. to ft.							
Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or gauge No. 124							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement			
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 ABS	12 None used (open hole)			
2 Louvered shutter	4 Key punched	7 Torch cut		13 Saw cut			
SCREEN-PERFORATED INTERVALS: From 60 ft. to 145 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other			
Grout Intervals: From 25 ft. to 13 ft., From ft. to ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
13 Insecticide storage							
Direction from well? West How many feet? 125							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG	
0	3	Soil					
3	5	Rock					
5	12	Clay					
12	25	Shale					
25	45	5% Limestone					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/18/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/yr) 7/18/86 by (signature) Clark Winter							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.							