

1 LOCATION OF WATER WELL:		Fraction County: <i>Butler</i>	NE $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 35	Township Number T 26 S	Range Number R 5 E
Distance and direction from nearest town or city street address of well if located within city? <i>from EL DORADO 4 1/2 S. on 54-77 1/2 west</i>						
2 WATER WELL OWNER:		<i>Donald McLAUGHLIN</i>		Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #:		<i>333 SIMPSON RD EL DORADO KS 67042</i>		Application Number:		
City, State, ZIP Code:						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 50 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. 20 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield 40 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes. No. ✓ If yes, mo/day/yr sample was submitted Water Well Disinfected Yes No				
5 TYPE OF BLANK CASING USED:		1 Steel 2 PVC	3 RMP (SR) 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (specify below)	CASING JOINTS: Glued Welded Threaded
Blank casing diameter		5 in. to		ft., Dia.	in. to ft., Dia.	in. to ft.
Casing height above land surface		13 in.		160 weight	lbs./ft.	Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 2 Brass		3 Stainless steel 4 Galvanized steel	5 Fiberglass 6 Concrete tile	7 PVC 8 RMP (SR) 9 ABS	10 Asbestos-cement 11 Other (specify) 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 2 Louvered shutter		3 Mill slot 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)	
SCREEN-PERFORATED INTERVALS:		From. 30	ft. to 50	ft., From	ft. to ft.	
GRAVEL PACK INTERVALS:		From. 20	ft. to 50	ft., From	ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout	3 Bentonite	4 Other		
Grout Intervals:		From. 3 ft. to 20	ft., From	ft. to ft., From	ft. to ft.	
What is the nearest source of possible contamination:						
1 Septic tank 2 Sewer lines 3 Watertight sewer lines		4 Lateral lines 5 Cess pool 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)	
Direction from well?						
FROM 0 8 15 30	TO 8 15 30 50	LITHOLOGIC LOG <i>Earth Brown Clay Red Clay Gray Shale</i>	FROM	TO	LITHOLOGIC LOG	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) *5/07/85* and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. *424* This Water Well Record was completed on (mo/day/year) *5/30/85* by (signature) *Jerry Reeser*

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.