


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction County Butler	NE $\frac{1}{4}$	Section Number 19	Twp Number T 26 S	Range Number R 6 EW	
Distance and direction from nearest town or city street address of well if located within city? <i>City of El Dorado is 3 miles northwest.</i>							
2 WATER WELL OWNER:		City of El Dorado P.O. Box 792 El Dorado, KS 67042					Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		 N W E S					MW 2
4 DEPTH OF COMPLETED WELL:		121	ft. ELEVATION: 1370.21' Ground				
Depth(s) Groundwater Encountered:		1. 1364.97	ft. 2.	1365.39	ft. 3.	ft.	
WELL'S STATIC WATER LEVEL 1365.39 ft below land surface measured on mo/day/yr 2/9/98							
Pump test data: Well water was NA ft. after _____ hours pumping gpm							
Est. Yield NA gpm: Well water was NA ft. after _____ hours pumping gpm							
Bore Hole Diameter 8 in. to 15 ft. and _____ in. to _____ ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes X No If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:							
1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped			
6 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded			
Blank casing diameter 7 in. to 2 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface Flush in. weight lbs./ft. Wall thickness or gauge No.							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement			
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)			
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	12 None used (open hole)			
SCREEN-PERFORATED INTERVALS: From 12 ft. to 2 ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From 12 ft. to 2 ft., From ft. to ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 2 ft. to 0 ft., From ft. to ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well			
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well			
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)			
13 Insecticide storage							
Direction from well? North How many feet? 5-10							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
0	6'	Black silty clay w/ iron stains, brown mottling, no odor, organics					
6	15'	Tan weathered limestone, fragmented, sand traces minor silty clay matrix, oxidation					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Jan 26, 98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 634 This Water Well Record was completed on (mo/day/yr) March 6, 98 under the business name of Shirley Env. Testing LLC by (signature) Shirley							