

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:

Section-Township-Range: 13

Fraction (1/4 1/4 1/4): SE NE

County: BUTLER

Location changed to:

13 - 26 S - 7 E

SE NE

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Butler Co ownership map and directions from Driller

initials: DS date: 8-31-04

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>	$\frac{1}{4}$ SE $\frac{1}{4}$ NE $\frac{1}{4}$	13	T	S R

Distance and direction from nearest town or city street address of well if located within city?

INTERSECTION OF SE 20TH & SE Gray Rd., Rosalia, KS

2 WATER WELL OWNER:	<u>MAGELLAN PIPELINE COMPANY, LLC</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #	<u>ONE WILLIAMS CENTER</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL..... <u>120'</u> ft. ELEVATION:
--	---

N W S E	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL..... ft. below land surface measured on mo/day/yr
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter. <u>B</u> in. to ft., and. in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes. No. ; If yes, mo/day/ys sample was submitted
	Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. Clamped.
1 Steel 2 PVC	3 RMP (SR) 4 ABS	6 Asbestos-Cement 7 Fiberglass	Welded. Threaded.

Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.Casing height above land surface. 30" in., weight lbs./ft. Wall thickness or gauge No. 40

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement
1 Steel 2 Brass	3 Stainless steel 4 Galvanized steel	8 RMP (SR) 9 ABS
5 Fiberglass 6 Concrete tile	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)
1 Continuous slot 2 Louvered shutter	3 Mill slot 4 Key punched	12	ft. to <u>2.5</u> ft., From ft. to ft.

SCREEN-PERFORATED INTERVALS: From. 12' ft. to 2.5 ft., From ft. to ft.

From. ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From. 12' ft. to 1.5 ft., From ft. to ft.From. 1.5 ft. to 1.5 ft., From ft. to ft.

Bent Seal

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete 5-0

Grout Intervals: From. ft. to ft., From. ft. to ft., From. ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)

Direction from well?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS