

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NW 1/4 NW 1/4 NW 1/4	Section Number 34	Township Number T 27 S	Range Number R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 1601 S. Hydraulic, Wichita, KS.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		Amoco Oil Co. 8700 Indian Creek Pkwy. Overland Park, KS. 66310			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 20'6" ft. ELEVATION: Depth(s) Groundwater Encountered 1.15' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 14.44' ft. below land surface measured on mo/day/yr 5-25-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter. 8 1/2" in. to 20'6" ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes..... No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2.375 in. to 10' ft., Dia in. to ft., Dia in. to SDR 13 ft. Casing height above land surface Flush in., weight lbs./ft. Wall thickness or gauge No. SCH 40		CASING JOINTS: Glued Clamped Welded Threaded... X TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20'6" ft. to 8 1/2" ft., From ft. to ft. From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 8 1/2' to 4' ③ ft., From 4' ③ to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? West How many feet? 100'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Grass- Blk silty sandy soil, roots, earthy odor.			
1	3.50	Brn sandy silty clay to clayey silty sand, moist, soft, root frag, no odor.			
3.50	11	Tan fine grained silty sand, dry, no odor.			
11	12	Med brn sandy clay len, moist, firm, no odor.			
12	15	Fine-coarse grained sand & gravel, no odor, poorly sorted.			
15	16	Gray silty sandy clay, soft, no odor.			
16	20'6"	Fine-coarse grained sand & gravel, wet, no odor, poorly sorted, subrounded-subangular.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-8-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-26-95 under the business name of JB Environmental Drilling by (signature) James Bieber					