


1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>13</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> <u>EW</u>
--	---	-----------------------------	----------------------------------	--------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

6327 E. 13th, Wichita, KS.

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<u>Amoco Oil Co.</u> <u>8700 Indian Creek Pkwy; Suite 190</u> <u>Overland Park, KS. 66210</u>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL <u>20'</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>6'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>5.0</u> ft. below land surface measured on mo/day/yr <u>6-23-95</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8 1/2"</u> in. to <u>20'</u> ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10</u> Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>
---	---

5 TYPE OF BLANK CASING USED: 1 Steel <u>2 PVC</u> Blank casing diameter <u>2.375</u> in. to <u>5'</u> Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR 13</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <u>3 Mill slot</u> 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From <u>20'</u> ft. to <u>5'</u> ft. From ft. to ft. GRAVEL PACK INTERVALS: From <u>20'</u> ft. to <u>4'</u> ft. From ft. to ft.	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u> 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)
---	---

6 GROUT MATERIAL: Grout Intervals: From <u>4'</u> ft. to <u>3'</u> ft. From <u>3'</u> ft. to <u>0'</u> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy <u>11</u> Fuel storage 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? <u>North</u> How many feet? <u>40'</u>	1 Neat cement 2 Cement grout 3 Bentonite 4 Other 10 Livestock pens 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
--	---

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Asphalt w/ sand underlayment			
1	4	Blk stiff clay, moist			
4	8	Med brn oxide stained & mottled clay, stiff, faint to mod. odor.			
8	12	Green-gray green gravelly clay, mottled, ls, rx, gravel & caliche, moist to wet, mod odor.			
12	14	Yellow brn-yellow gray shaley clay, moist to dry,			
14	16	Red brn clay, dry to moist, stiff, no odor.			
16	20	Olive clay to shaley clay, moist, stiff, no odor.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (<u>1</u> constructed) (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-10-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>6-28-95</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James B. Boker</u>
--