1 LOCATION OF WATE		FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212		1 -	
نـــا					Section Number		Ra	ange Number
Sedgwi		NE 1/4 street address of well if loca	NE 1/4 S	W 1/4	32	T 27 s	R	1E E/W
I .	•		·			,		
1902 Exc		<u>Wichita,</u> AND, Erick						
RR#, ST. ADRESS, BO			•			Board of Agric	ulture, Divivsion of W	ater Resource
RRM, ST. ADRESS, BOXW: 3019 W. 17th CITY, STATE, ZIP CODE: Joplin, MO.				64801 Application Number:			,	
3 LOCATE WELL'S LOC		DEPTH OF CO	LEAD WELL	24		LEVATION:	n I vaniver .	
AN "X" IN SECTION E		Depth(s) groundw		1	n.	2 ft.	3	ſt.
	T I V	WELL'S STATIC W	ATER LEVEL 15	FT.	BELOW LAND	SURFACE MEASURED ON mo/d	1 09/jr	07/1995
ww	NE.	Pump test	t data: Well w	ater was	n.	after hour	rs pumping	gpm
1 1 7	1 1 1 1	est. Yield	•	ater was	ft.	after hour	rs pumping	gpm
ž w		ا lore Hole Diameter سام		to	ft.	and	in. to	ft.
	"	vell water 184		Public water		8 Air conditioning	11 Injection w	
sw	sps	1 Domestic		Oil field wat	•	9 Dewatering	12 Other (Spe	cify below)
		2 Irrigation	ŕ	Lawn and ga		10 Monitoring well	, • · (3/	
 	2 1	Was a chemical/bacte submitted	eriological sample sub	mitted to Dep	•	s No 🗶 ; If Vater Well Disinfected?	f yes, mo/day/yr s	sample was No
5 TYPE OF CASI		Subinitien	E Wannahé iman	•	Concrete tile	CASING JOINTS:	Yes X	
1 Steel	3 RMP (SR)		5 Wrought iron 6 Asbestos-Cement	_	Concrete tile Other (Specif		: Glued Welded	Clamped
2 PVC	4 ABS		7 Fiberglass	, ,,	Juier (Speen)	y Delow)	Threaded	
Blank casing Diamete		ln. to	ft., Dia	in.	to	ft. Dia	in. to	ſt.
Casing height above	, -		п., ыла weight		to lbs. / ft.	Wall thickness or gauge		14.
TYPE OF SCREEN			J		PVC	10 Asbesto		
1 Steel 3	3 Stainless Steei		5 Fiberglass 8 RMP (SR) 11 other (specify) N/A					'A
2 Brass 4	4 Galvanized steel		6 Concrete tile 9 ABS 12 !			12 None u	None used (open hole)	
SCREEN OR PERF	ORATION OPEN	ING ARE:	5 Gauzed wrapped		8 Saw cut 11 None (open hole)			
1 Continous slot	3 Mill slot		6 Wire v	6 Wire wrapped				
2 Louvered shutter	4 Key pun	ched	7 Torch	cut		10 Other (specify)	N/A	
SCREEN-PERFORA	ATION INTERVA	LS: from	ft. (to	ft., Fr	om	ft. to	ft.
		from	n.	to	ft., Fr	•	ft. to	ft.
GRAVEL	PACK INTERVA	ALS: from		ft. to ft., Fi		~	ft. to	ft.
ļ		from	ft.	to	ft., Fr	om	ft. to	<u>r</u>
6 GROUT MATER	_		ement grout	3 Beni	tonite	4 Other		
Grout Intervals: From What is the nearest se		ft. to 24	ft. From	ft. From ft. to ft. From 10 Livestock pens		ft. From	ft. to	ft.
1 Septic tank	ource of possible co 4 Lateral l		7 Pit privy			stock pens l storage	14 Abandon w	
2 Sewer lines	4 Lateral intes			8 Sewage lagoon		tilizer storage	15 Oil well/Gas well 16 Other (specify below)	
3 Watertight sewer	5 Cess po lines 6 Seepage		9 Feedyard	12 Importation at a many		attatila atamana	None Apparent	
Direction from well?		e pu) i ctuya.u			How many feet?	loue whhe	Trenc
FROM TO		ITHOLOGIC LOG		FROM	ТО		INTERVALS	
				0	24	cement grout		
								
					d, (2) recons	tructed, or (3) plugged u		
was completed on	(mo/day/year)	09/07/	199 <u>5 </u>	nd this reco	d, (2) recons	tructed, or (3) plugged u	je and belief. K	ansas Water
was completed on Well Contractor's	(mo/day/year) License No	09/07/ 236	199 <u>5 </u>	and this reco	d, (2) recons	tructed, or (3) plugged un the best of my knowledg (mo/day/yr)Ω	je and belief. K	ansas Water