

1 LOCATION OF WATER WELL:		Fraction 10 ¹ / ₄ NW ¹ / ₄ NE ¹ / ₄ NW ¹ / ₄	Section Number 17	Township Number T 27 S	Range Number R 1 E
County: SEDGWICK					
Distance and direction from nearest town or city street address of well if located within city? 60' SOUTH & 90' EAST OF SW COR. BITTING & 13TH ST. MW-7					
2 WATER WELL OWNER: JAMES GOOLSBY		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 547 N. HANDLEY		Application Number:			
City, State, ZIP Code: WICHITA, KANSAS 67203					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20 ft. ELEVATION: 1307.22			
		Depth(s) Groundwater Encountered 1. 14.5 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 14.49 ft. below land surface measured on mo/day/yr 10/18/95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to 20 in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>NO</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>NO</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
5 Wrought iron 8 Concrete tile					
6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter 2 in. to 10 ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 2 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 20 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 2 ft. to 8 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? Northwest		How many feet? 110			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Fill Sand			
5	6	Silty Clay, dark brown			
6	7	Sand, Fine to medium			
7	8	Silty Clay, dark brown			
8	9	Sand, Fine to medium			
9	10	Silty Clay, dark brown			
10	11	Sand, Fine to medium			
11	12	Silty Clay, dark brown			
12	15	Sand, Fine to medium			
15	20	Sand & gravel, saturated			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 10/11/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 524 This Water Well Record was completed on (mo/day/yr) 10/30/95 under the business name of ALLIED LABORATORIES by (signature) Robert B. Brownell					