

1 LOCATION OF WATER WELL: County: Sedgwick	Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 21	Township Number T 27 S	Range Number R 1 EW
--	--------------------------------------	--------------------------	-------------------------------	-----------------------------------

Distance and direction from nearest town or city street address of well if located within city?
603 S. Broadway, Wichita, KS.

2 WATER WELL OWNER: Amoco Oil Co. RR#, St. Address, Box #: 8700 Indian Creek Pkwy Suite 190 City, State, ZIP Code: Overland Park, KS. 66210	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 23'6" ft. ELEVATION:
--	---

Diagram of a section box divided into four quadrants: NW, NE, SW, and SE. An 'X' is marked in the SW quadrant. A north arrow points upwards.

Depth(s) Groundwater Encountered 1. **14'6"** ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL **13'6"** ft. below land surface measured on mo/day/yr **1-3-96**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter **8'6"** in. to **23'6"** ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ☒ No ☒

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile
1 Steel	6 Asbestos-Cement	9 Other (specify below)
2 PVC	7 Fiberglass	
3 RMP (SR)		
4 ABS		
Blank casing diameter 2.375 in. to 13' ft. Dia		
Casing height above land surface Flush Ht. in. weight		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile
SCREEN OR PERFORATION OPENINGS ARE:		
1 Continuous slot	3 Mill slot	5 Gauzed wrapped
2 Louvered shutter	4 Key punched	6 Wire wrapped
SCREEN-PERFORATED INTERVALS:		
From 23' ft. to 13' ft.		
GRAVEL PACK INTERVALS:		
From 23'6" ft. to 11'6" ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout
Grout Intervals: From 11'6" ft. to 5' ft.		
What is the nearest source of possible contamination:		
1 Septic tank	4 Lateral lines	7 Pit privy
2 Sewer lines	5 Cess pool	8 Sewage lagoon
3 Watertight sewer lines	6 Seepage pit	9 Feedyard
Direction from well? West North West		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Asphalt			
.50	3.25	Dk-med brn clay, oxide stained, root frag., moist, no odor.			
3.25	8	Med-red brn clay to sandy clay, mottled w/ gray brn clay, moist, no odor, fine grained sand.			
8	15.50	Fine grained red brn sand, qtz, feldspar, dry, no odor.			
15.50	23'6"	Fine-coarse grained sand & gravel, wet, no odor, well graded.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-3-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 1-8-96 under the business name of JB Environmental Drilling by (signature) James Beber	
--	--

OFFICE USE ONLY