

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NE ¼ NW ¼ ¼	32	T 27 S	R 1

Distance and direction from nearest town or city street address of well if located within city?  
560 feet Southwest of center line of Harry Street and Greenway in Wichita, Kansas

2	WATER WELL OWNER:	Harpool Brothers	
	RR#, St. Address, Box # :	4141 N. Edgemoor Street	Board of Agriculture, Division of Water Resources
	City, State, ZIP Code :	Wichita, Kansas 67220	Application Number:

**LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:**

NW	X	NE
SW		SE

1 Mile

**DEPTH OF COMPLETED WELL.** 15.0 ft. **ELEVATION:** N/A

Depth(s) Groundwater Encountered 1. 10.2 ft. 2. . ft. 3. . ft.

**WELL'S STATIC WATER LEVEL** 10.2 ft. below land surface measured on mo/day/yr 2-15-96

Pump test data: Well water was . ft. after . hours pumping . gpm

Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm

Bore Hole Diameter . 12 . in. to . 8 . ft., and . in. to . ft.

**WELL WATER TO BE USED AS:**

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		9 Dewatering
		10 Monitoring well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes \_\_\_\_\_ No \_\_\_\_\_; If yes, mo/day/yr sample was submitted \_\_\_\_\_

Water Well Disinfected? Yes \_\_\_\_\_ No \_\_\_\_\_

5 TYPE OF CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued	Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below) stainless steel	Welded	
		7 Fiberglass		Threaded	

Blank casing diameter 2 in. to 10 ft., Dia. in. to ft., Dia. in. to ft.

Casing height above land surface 0 in., weight 3.65 lbs./ft. Wall thickness or gauge No. sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 10.0 ft. to 15.0 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 8.0 ft. to 15.0 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 0 ft. to 5.0 ft., From 5.0 ft. to 8.0 ft., From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)  
Direction from well? Northeast How many feet? 500

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-15-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 592 This Water Well Record was completed on (mo/day/yr) 2-28-96 under the business name of Enviro Tech Services, Inc. by (signature) [Signature]