


LOCATION OF WATER WELL: County: SEDGWICK	Fraction SW 1/4 SW 1/4 NW 1/4	Section Number 23	Township Number T 27 S	Range Number R 1
Distance and direction from nearest town or city street address of well if located within city? 140 NORTH HILLSIDE wichita, KS				

MW#5

EAST

WATER WELL OWNER: TOWN&COUNTRY	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: City, State, ZIP Code: P.O. BOX 17087 WICHITA, KS	67217 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	DEPTH OF COMPLETED WELL: 44' ft. ELEVATION: Depth(s) Groundwater Encountered 1. 35' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/4 in. to 44 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
--	--

TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter 2 in. to 29 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 0 in., weight sched. 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 010 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 44 ft. to 29 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 44 ft. to 24 ft. From ft. to ft. From ft. to ft. From ft. to ft.
---

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 22 ft. to 0.3 ft. From 24 ft. to 22 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? north How many feet? 45'
--

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	grass topsoil DARK brn clay			
5	12	DARK BRN STIFF CLAY			
12	18	SILTY SANDY LIGHT BRN TO GREY CLAY MED PLASTIC			
18	25	SILTY SANDY REDDISH BROWN CLAY			
25	28	LIGHT BROWN TO TAN CLAYEY SAND FINE 80% sand			
28	38	as ABOVE WITH MED TO COARSE SAND MOSTLY SAND AND SATURATED AT 35'			
38	44	MED TO COARSE SAND VERY WET			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-18-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 4-3-96 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)
--