

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW 1/4 SW 1/4 NW 1/4	Section Number 23	Township Number T 27 S	Range Number R 1 E																																																												
Distance and direction from nearest town or city street address of well if located within city? 140 NORTH HILLSIDE WICHITA, KS																																																																	
2 WATER WELL OWNER: TOWN&COUNTRY RR#, St. Address, Box # : City, State, ZIP Code : P.O. BOX 17087 WICHITA, KS 67217																																																																	
Board of Agriculture, Division of Water Resources Application Number:																																																																	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"> </div>		4 DEPTH OF COMPLETED WELL: 43.5 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 35 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/4 in. to 43.5 ft. and in. to ft. WELL WATER TO BE USED AS: <div style="display: flex; justify-content: space-between;"> <div> 5 Public water supply 1 Domestic 2 Irrigation </div> <div> 3 Feedlot 4 Industrial </div> <div> 6 Oil field water supply 7 Lawn and garden only </div> <div> 8 Air conditioning 9 Dewatering 10 Monitoring well </div> <div> 11 Injection well 12 Other (Specify below) </div> </div> Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No																																																															
5 TYPE OF BLANK CASING USED: <div style="display: flex; justify-content: space-between;"> <div> 1 Steel 2 PVC </div> <div> 3 RMP (SR) 4 ABS </div> <div> 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass </div> <div> 8 Concrete tile 9 Other (specify below) </div> </div> Blank casing diameter 2 in. to 28.5 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface 0 in., weight SCHED. 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: <div style="display: flex; justify-content: space-between;"> <div> 1 Steel 2 Brass </div> <div> 3 Stainless steel 4 Galvanized steel </div> <div> 5 Fiberglass 6 Concrete tile </div> <div> 8 RMP (SR) 9 ABS </div> <div> 10 Asbestos-cement 11 Other (specify) </div> <div> 12 None used (open hole) </div> </div> SCREEN OR PERFORATION OPENINGS ARE: <div style="display: flex; justify-content: space-between;"> <div> 1 Continuous slot 2 Louvered shutter </div> <div> 3 Mill slot 010 4 Key punched </div> <div> 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut </div> <div> 8 Saw cut 9 Drilled holes 10 Other (specify) </div> <div> 11 None (open hole) </div> </div> SCREEN-PERFORATED INTERVALS: From 43.5 ft. to 28.5 ft., From ft. to ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 43.5 ft. to 25 ft., From ft. to ft., From ft. to ft., From ft. to ft.																																																																	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 22 ft. to -0.3 ft., From 25 ft. to 22 ft., From ft. to ft. What is the nearest source of possible contamination: <div style="display: flex; justify-content: space-between;"> <div> 1 Septic tank 2 Sewer lines 3 Watertight sewer lines </div> <div> 4 Lateral lines 5 Cess pool 6 Seepage pit </div> <div> 7 Pit privy 8 Sewage lagoon 9 Feedyard </div> <div> 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage </div> <div> 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) </div> </div> Direction from well? north How many feet? 67																																																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>5</td> <td>topsoil</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>brown to dark brown clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>10</td> <td>silty brown clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>15</td> <td>dark brown to grey clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>20</td> <td>sandy silty light brn to tan clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>20</td> <td>28</td> <td>light brn sandy clay iron stringers & staining</td> <td></td> <td></td> <td></td> </tr> <tr> <td>28</td> <td>32</td> <td>clayey sand tan fine to MED</td> <td></td> <td></td> <td></td> </tr> <tr> <td>32</td> <td>40</td> <td>MED sandy saturated at 35.5</td> <td></td> <td></td> <td></td> </tr> <tr> <td>40</td> <td>43.5</td> <td>med to coarse sand</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	5	topsoil						brown to dark brown clay				5	10	silty brown clay				10	15	dark brown to grey clay				15	20	sandy silty light brn to tan clay				20	28	light brn sandy clay iron stringers & staining				28	32	clayey sand tan fine to MED				32	40	MED sandy saturated at 35.5				40	43.5	med to coarse sand			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																																												
0	5	topsoil																																																															
		brown to dark brown clay																																																															
5	10	silty brown clay																																																															
10	15	dark brown to grey clay																																																															
15	20	sandy silty light brn to tan clay																																																															
20	28	light brn sandy clay iron stringers & staining																																																															
28	32	clayey sand tan fine to MED																																																															
32	40	MED sandy saturated at 35.5																																																															
40	43.5	med to coarse sand																																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (X) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-18-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 4-2-96 under the business name of KYRTZ ENVIRONMENTAL SERVICE by (signature)																																																																	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																	

OFFICE USE ONLY

T

R

EAW

SEC.

1/4

1/4

1/4