

1 LOCATION OF WATER WELL: County: Sedgwick	Fraction NE 1/4 NW 1/4 NE 1/4	Section Number 31	Township Number T 27 S	Range Number R 1 E/W
--	--------------------------------------	--------------------------	-------------------------------	-----------------------------

Distance and direction from nearest town or city, street address of well if located within city?
1624 W. Harry St., Wichita, KS.

2 WATER WELL OWNER: Rick Ott/dba Rick's Appliance RR#, St. Address, Box #: 1624 W. Harry City, State, ZIP Code: Wichita, KS.	Board of Agriculture, Division of Water Resources Application Number:
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 20'6" ft. ELEVATION:
--	---

1 Mile

Depth(s) Groundwater Encountered **1.13 1/2'** ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL **12.80** ft. below land surface measured on mo/day/yr **4-12-96**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter **8 1/2"** in. to **20'6"** ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes.....No **X**.....; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes **No**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile
1 Steel	6 Asbestos-Cement	9 Other (specify below)
2 PVC	7 Fiberglass	
3 RMP (SR)		
4 ABS		
Blank casing diameter 2.375 in. to 10' ft., Dia		
Casing height above land surface Flush Mt. in., weight		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
1 Steel	5 Fiberglass	10 Asbestos-cement
2 Brass	6 Concrete tile	11 Other (specify)
3 Stainless steel	8 RMP (SR)	12 None used (open hole)
4 Galvanized steel	9 ABS	
SCREEN OR PERFORATION OPENINGS ARE:		
1 Continuous slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	6 Wire wrapped	11 None (open hole)
3 Mill slot	7 Torch cut	
4 Key punched		
SCREEN-PERFORATED INTERVALS:		
From 20' ft. to 10' ft.		
GRAVEL PACK INTERVALS:		
From 20'6" ft. to 8' ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout
Grout Intervals: From 8' ft. to 6' ft.		
What is the nearest source of possible contamination:		
1 Septic tank	4 Lateral lines	7 Pit privy
2 Sewer lines	5 Cess pool	8 Sewage lagoon
3 Watertight sewer lines	6 Seepage pit	9 Feedyard
Direction from well? North North East		
		How many feet? 140'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Asphalt			
.50	4	Dk brn silty clay to clay, no odor, moist, firm, low plasticity, w/trace amt. of sand oxides.			
4	13	Fine grained silty sand to sand, dry, no odor, oxides, well sorted sand.			
13	20'6"	Fine-coarse grained sand w/ trace amt. of gravel, wet, no odor, poorly sorted.			

F.M. OK'd by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-11-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 . This Water Well Record was completed on (mo/day/yr) 4-15-96 under the business name of JB Environmental Drilling by (signature) <i>James Becker</i>	
---	--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.