

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>		Fraction <u>NE</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NE</u> $\frac{1}{4}$	Section Number <u>31</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>1624 W. Harry St., Wichita, KS.</u>					
2 WATER WELL OWNER: <u>Rick Ott</u> RR#, St. Address, Box #: <u>1624 W. Harry</u> City, State, ZIP Code: <u>Wichita, KS.</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>20'6"</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1'4"</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>13.09</u> ft. below land surface measured on mo/day/yr <u>4-12-96</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>8 1/2"</u> in. to <u>20'6"</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No <u>(No)</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 <u>PVC</u>		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded: <u>X</u>
Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft., Dia in. to ft., Dia in. to SDR <u>13</u> ft.					
Casing height above land surface: <u>Flush Ht.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH. 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 <u>Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From <u>20'</u> ft. to <u>10'</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>20'6"</u> ft. to <u>8'</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other					
Grout Intervals: From <u>8'</u> ft. to <u>6'</u> ft., From <u>6'</u> ft. to <u>0'</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 <u>Fuel storage</u> <u>Fueler</u>	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>North west</u> How many feet? <u>170'</u>					
FROM		TO	LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS
0	1		Gravelly clay, road pack, ls.rx.,qtz gravel, moist-dry.		
1	4		Dk brn clay, tight, dry,		
4	6		Dk-med brn clayey sandy silt w/ dk brn silty banding, dry to moist.		
6	13.50		Fine grained sand w/ some silty sand, dry, well rounded.		
13.50	20'6"		Fine-coarse grained sand w/ some pebbly gravel, wet, no odor, poorly sorted, sub rounded grains.		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>4-11-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>4-15-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Boker</u>					