

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SE 1/4 SE 1/4 SW 1/4	Section Number 5	Township Number T 27 S	Range Number R 1 E
Distance and direction from nearest town or city street address of well if located within city? 618 W. 21st. Wichita, Ks.					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Larry Schaar/Universal Motor Fuels 2824 N. Ohio Wichita, Ks. 67219			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL 20'6" ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1.13 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 12.35 ft. below land surface measured on mo/day/yr 4-17-96 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8'6" in. to 20'6" ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
4 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2.375 in. to ft., Dia in. to ft., Dia in. to ft. Casing height above land surface Flush Mt. in., weight lbs./ft. Wall thickness or gauge No. SDR 13 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 20'6" ft. to 8' ft., From ft. to ft. From ft. to ft., From ft. to ft.		CASING JOINTS: Glued Clamped Welded X Threaded SDR 13 SCH 40			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 8' ft. to 4' ft., From 4' ft. to 0' ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? East How many feet? 70'			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	.50	Gravel			
.50	5	Dk brn tight clay w/ trace amt. of oxides, sand, dry, no odor, root frag.			
5	13.25	Yellow-white fine to very fine dry sand, well rounded & sorted.			
13.25	20'6"	Fine-coarse grained sand w/ some gravel, wet, poorly sorted, sub rounded grains, no odor.			
		F.H. OK'd by Don Taylor			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-16-96 and this record is true to the best of my knowledge and belief. Kansas Water Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-4-96 under the business name of JB Environmental Drilling by (signature) James Becker					