LOCATION	OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212		T	
					Section Number	Township Number	Range Number	
	dgwick	NE 1/4		E 1/4	30	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?								
1616	Dayton	Wichita, I	Kansas					
WATERV	WELL OWNER: WEST		CH OF GOD					
RR#, ST. Al	DRESS, BOX#: 1900	McCormick	3			Board of Agriculture, D	tvivsion of Water Resource	
CITY, STA		ita, Kansa			67213	Application Numbe	r:	
	ELL'S LOCATION WITH	DEPTH OF	HEGERWELL	18.5		LEVATION:		
	SECTION BOX:	Depth(s) groundw	- •	1	ft.	2 ft.	3 ft.	
		WELL'S STATIC W				SURFACE MEASURED ON mo/day/yr	07/25/1996	
	·	Pump tes		vater was	ft.	after hours pum		
		Est. Yield		water was	ft.	after hours pum		
w W	1 1 1	Bore Hole Diameter (to	ft.	and in.	to ft.	
≦ "		WELL WATER 1	SUSED AS:	5 Public water			njection well	
1.		1 Domestic		6 Oil field was		•	Other (Specify below)	
	SW SE	2 Irrigation		7 Lawn and g		10 Monitoring well	Autor (albania)	
		Was a chemical/bacte				ū	o/day/yr sample was	
· -	S	submitted	eriological sample su	Difficent to De	_			
5 TYPE O	OF CASING USED:	Subliffice						
1 Steel	3 RMP (SR)		5 Wrought iron 6 Asbestos-Cemer	_	Concrete tile	=	lued Clamped	
	` ,			. 9	Other (Specify	,	Velded	
2 PVC	4 ABS		7 Fiberglass			1	hreaded	
Blank casing	DASEMENT CLASS	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
			weight	_	lbs. / ft.	Wall thickness or gauge No.	4	
	CREEN OR PERFORAT	TON MATERIAL:	5 Fiberglass		PVC DMD (SD)	10 Asbestos-ceme		
1 Steel	3 Stainless Steel		ū		RMP (SR)	11 other (specify	M/A	
2 Brass	4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (op	en hole)	
1	R PERFORATION OPE	NING ARE:		ed wrapped		8 Saw cut	11 None (open hole)	
1 Continous	slot 3 Mill slo	t	6 Wire	wrapped		9 Drilled holes		
2 Louvered s	shutter 4 Key pu	nched	7 Torch	cut		10 Other (specify)	/A	
SCREEN-PE	ERFORATION INTERVA	ALS: from	ft.		ft., Fro	·	ft.	
		from			ft., Fro		ft.	
GRAVEL PACK INTERVALS: from		ft. to ft., Fr ft. to ft., Fr			ft.			
		from		to	ft., Fro		ft.	
6 GROUT	MATERIAL: 1 Neat co		Cement grout		tonite	4 Other		
Grout Intervals: From 0 ft. to 6 ft. From ft. to					ft. From	ft. to ft.		
What is the nearest source of possible contamination:					estock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines		l lines	7 Pit privy		11 Fuel	rtomoro.	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		mal	8 Sewage lagoon		12 Ferti		Other (specify below)	
3 Watertight sewer lines 6 Seepage pit			9 Feedyard	13 Importante storage			(- I)	
Direction from well? North How many feet? 4								
FROM T		ITHOLOGIC LOG		FROM	то	PLUGGING INTER	RVALS	
				0	6	cement grout		
		1.1.1.7		6	8	bentonite hole	plug	
			1.	8	18.5	chlorinated san		
		***************************************			120.5	OHIOIIMUOG Bun	u unu gruvor	
					1			
				1	1			
			191.0		 			
		- Lawrence					46.	
				-				
					 	1.00		
					-			
						A. C.		
7 CONTRA	ACTOR'S OR LANDOWNER	'S CERTIFICATION: Th	is water well was (1) constructe	ed. (2) recons	tructed, or (3) plugged under n	ny jurisdiction and	
CONTR	ACTOR'S OR LANDOWNER	's CERTIFICATION: Th	is water well was (* 1996	1) constructe	ed, (2) reconst	tructed, or (3) <u>plugged</u> under n the best of my knowledge and	ny jurisdiction and belief. Kansas Water	
was compl Well Contr	leted on (mo/day/year) ractor's License No	07/25/ 236	1996 This Water Well Ro	and this rec	ord is true to empleted on (the best of my knowledge and mo/day/yr)	belief. Kansas Water	
was compl Well Contr	leted on (mo/day/year)	07/25/ 236	1996 This Water Well Ro	and this rec	ord is true to empleted on (the best of my knowledge and mo/day/yr)	belief. Kansas Water 5./9.6	