1 LOCATION OF WATER WELL: FRACTIO			FRACTION	Water Well Recor	d Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
			CW	CT-T 1/4		•	1 15		
Sedgwick SE 1/4 SW 1/4 SW 1/4 31 T 27 S R 1E E/W Distance and direction from nearest town or city street address of well if located within city?									
l · · · · · · · · · · · · · · · · · · ·									
-					le of E	verett	Wichita, Kans	as	
WATER WELL OWNER: WICHITA, CITY OF									
RR#,	ST. ADRESS,		Wain				Board of Agriculture, Divivision of Water Resource		
СІТУ	STATE, ZIP	code: Wich:	ita, Kansa				Application Number: 29357		
		OCATION WITH 4	DEPTH OF COM	APLETED WELL	35	ft. ELI	EVATION:		
AN "X	' IN SECTION	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
		v	WELL'S STATIC W	ATER LEVEL 1	2 FT	. BELOW LAND SU	RFACE MEASURED ON mo/day/yr	06/05/1996	
	NW	NE	Pump test	data: Well	water was	ft.	after hours pum	ping gpm	
_		- i- I	st. Yield	gpm: Well	water was	ft.	after hours pum	ping gpm	
M M			ore Hole Diameter	12 in.	to 35	ft.	and in.	to ft.	
= "			VELL WATER TO	BE USED AS:	5 Public wate	r supply	8 Air conditioning 11 I	njection well	
١.			1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12 C	Other (Specify below)	
	Sw		2 Irrigation	4 Industrial	4 Industrial 7 Lawn and garden only 10 Monitoring well				
	X	v	Vas a chemical/bacte	riological sample s	ubmitted to D	epartment? Yes	No X ; If yes, m	o/day/yr sample was	
S submitted Water Well Disinfected? Yes X No									
5 TY	PE OF CA	SING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	lued X Clamped	
1 Stee	l	3 RMP (SR)		6 Asbestos-Cement 9 Other (Specif			·		
2 PVC		4 ABS		7 Fiberglass	S	DR-26	T	hreaded	
	_ sing Diam		n. to 20	ft., Dia	in.		ft., Dia in.	to ft.	
ı	•	ve land surface 12		,		lbs. / ft.	Wall thickness or gauge No.	.332	
Casing height above land surface 12 in., weight 5.594 lbs./ft. Wall thickness or gauge No332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Bras	ıs	4 Galvanized steel		6 Concrete tile	9	9 ABS	12 None used (or		
		REPORATION OPEN	INC ADE	5 Con	zed wrapped		8 Saw cut	11 None (open hoie)	
	n OR FEF nous slot	3 Mill slot			e wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 20 ft. to 3						ft., Fron	n ft. to	ft.	
from				ft. to		ft., Fron	n ft. to	ft.	
GRAVEL PACK INTERVALS: from 20				ft. to 35		ft., Fron	m ft. to	ft.	
<u> </u>			from	f	t. to	ft., Fron			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Ir	tervals:	From ()	ft. to 20	ft. From	ft.	to	ft. From	ft. to ft.	
What is the nearest source of possible contamination:			:		10 Livesto	ock pens 14 A	14 Abandon water well		
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel st	130	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool			8 Sewage lagoon				16 Other (specify below)		
3 Wate	rtight sewe	er lines 6 Seepage	e pit	9 Feedyard 13 In		13 Insect	ecticide storage None Apparent		
Direction from well?									
FROM	TO	LI	THOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS	
0	4	topsoil							
4	15	clay							
15	35	medium co	arse sand						
						 -			
					L		· · · · · · · · · · · · · · · · · · ·		
⁷ CO	TRACTO	R'S or landowner:	S CERTIFICATION: Th	is water well was	(1) construc	ted, (2) reconsti	ructed, or (3) plugged under r	ny jurisdiction and	
was completed on (mo/day/year)									
Well Contractor's License No									
Under the business name of Harp									