Location of the second	TD (CTTO)	Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number
Sedgwick	SW 1/4	NW 1/4 N	E 1/4	28	T 27 s	R 1E EW
Distance and direction from nearest town or city street address of well if located within city?						
714 S. Ida N	Wichita, F	lancac				
	Y, Vineno	ıa			Board of Australiana D	ivivsion of Water Resource
	. Ida				Board of Agriculture, D	With Stoll of Water Resource
	ta, Kansa	S			Application Numbe	r:
LOCATE WELL'S LOCATION WITH 4N "X" IN SECTION BOX:	DEPTH OF	WELL	29	ft. EL	EVATION:	
AN "A" IN SECTION BOX:	Depth(s) groundwa	ater Encountered	1	ft.	2 ft.	3 ft.
l l l v	VELL'S STATIC W.	ATER LEVEL 17	FT.	BELOW LAND SU	RFACE MEASURED ON mo/day/yr	06/14/1996
NW K NE	Pump test	data: Well w	vater was	ft.	after hours pum	ping gpm
	st. Yield	gpm: Well v	water was	ft.	after hours pum	
E Be	ore Hole Diameter	in Chown in.	to	ft.	and in.	to ft.
= "	ELL WATER 46		5 Public wate	r supply	8 Air conditioning 11 Is	njection well
	1 Domestic		6 Oil field wa			Other (Specify below)
SwSE	2 Irrigation		7 Lawn and g		10 Monitoring well	(-1,
					8	o/dov/vm sample was
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was						
submitted Water Well Disinfected? Yes X No TYPE OF CASING USED: 5 TYPE OF CASING USED:						
		5 Wrought iron		Concrete tile		lued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cemer	ıt 9	Other (Specify b	elow) V	Velded
2 PVC 4 ABS		7 Fiberglass			T	hreaded X
Blank casing Diameter 1 1/4 in	ı. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 36	in.,	weight		lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION			7	PVC	10 Asbestos-ceme	ent
4 CALL COLLEGE SWAP (SD)) N/A
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						M/A
	INC ADE.				8 Saw cut	11 None (open hole)
SCREEN OR PERFORATION OPEN 1 Continuus slot 3 Mill slot	5 Gauzed wrapped			11 None (open noie)		
I - I - I - I - I - I - I - I - I - I -		6 Wire	6 Wire wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punc	7 Torch	cut		10 Other (specify)	/A	
SCREEN-PERFORATION INTERVAL	LS: from	ft.	to	ft., Fron	n ft. to	ft.
	from	ft.	to	ft., Fron	n ft. to	ft.
GRAVEL PACK INTERVALS: from				ft., From		ft.
from				ft., Fron		ft.
6 GROUT MATERIAL: 1 Neat cen		ement grout		tonite		hole plug
	ft. to 6	ft. From	•	4-		
What is the nearest source of possible contamination:		ft. From ft. to 10 Lives		ft. From ock nens 14 A	ft. to ft. bandon water well	
1 Septic tank 4 Lateral lines				11 Fuel st		
- Paretta mics		• •			130	oil well/Gas well
C Cess poor		42 7			16 Other (specify below)	
	e pit	9 Feedyard		10 228000	9	
Direction from well? South					How many feet? 15	
FROM TO LIT	THOLOGIC LOG		FROM	то	PLUGGING INTE	<u>tVALS</u>
	****		0		cement grout	
	(4)		6		bentonite hole	
			20	29	chlorinated san	<u>d and gravel</u>
	700					
			 			
				 		
			1		ANALYSIA ANA	
7				<u> </u>		
7 CONTRACTOR'S OR LANDOWNER'S	CERTIFICATION: The	s water well was (*	1) construct	ed, (2) reconstr	ucted, or (3) plugged under n	ny jurisdiction and
was completed on (mo/day/year)						
Well Contractor's License No	(JD	This Water Well Re	ecord was c	ompleted on (n	no/day/yr)	(./. .
Under the business name of Harp Well & Pump Service. Inc by (signature) Todd & Harp						
					Jodd X	Hann