				Water Well Record	Form WWC-5	KSA 82a-1212			
1 LOCATI	ON OF WA	ATER WELL:	FRACTION			Section Number	Township Number	Range Number	
s	Sedgy	vick	NW 1/4	NW 1/4 N	€ 1/4	18	T 27 s	R 1E E/W	
Distance an	d direction	frem nearest town or cit	ty street address of well if k	ocated within city?					
125	57 N.	Coolidg	e Wic	hita, Kansa	as				
	ER WELL		MERVIL, Li						
RR#, ST	. ADRESS		7 N. Cooli				Board of Agriculture, l	Divivsion of Water Resource	
CITY, S	TATE, ZIF	CODE: Wic	hita, Kans				Application Numb	er:	
		LOCATION WITH	4 DEPTH OF	MILE WELL	24	ft. E	LEVATION:		
AN "X" I	N SECTIO	N BOX:	Depth(s) ground	water Encountered	1	ft.	2 ft.	3 ft.	
		X		WATER LEVEL 20	FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	06/10/1996	
	<b>NW</b>	NE	Pump te	est data: Well wa	ater was	ft.	after hours pur	nping gpm	
و	i		Est. Yield	91	ater was	ft.	after hours pur	• •	
MIIe M		E	Bore Hole Diameter		0	ft.	and tn.	to ft.	
-			WELL WATER 16		Public water			Injection well	
1	sw	sie	1 Domestic		Oil field wa		· ·	Other (Specify below)	
			2 Irrigation		Lawn and g		10 Monitoring well		
+ L		<u>                                    </u>		teriological sample sub	mitted to De	-		no/day/yr sample was	
- my/m	T O T O		submitted				Vater Well Disinfected? Yes		
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
1 Steel		3 RMP (SR)		6 Asbestos-Cement	, 9	Other (Specify	,	Welded	
2 PVC		4 ABS		7 Fiberglass				Threaded <b>X</b>	
		neter 1 1/2	in, to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height book and surface 60 in., weight lbs./ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel	SCREE	3 Stainless Steel	.IION MAIERIAL:	5 Fiberglass		PVC RMP (SR)	11 other (specif		
2 Brass		4 Galvanized stee	ام	6 Concrete tile		ABS	12 None used (o	M/A	
	OD DE					ADO	8 Saw cut	11 None (open hole)	
SCALEN ON TERFORATION OF ENING ARE: SCALE WIPPEU								11 None (open note)	
5 Min slot									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A									
SCREEN-	-PERFO	RATION INTERV	2	ft. 1	to	ft., Fro		ft.	
	~~		from	ft.		ft., Fr		ft.	
	GRAV	EL PACK INTER		ft.		ft., Fr			
6 GPOI	T MAT	EDIAL 1 Neat	cement 2	Cement grout		ft., Fr	4 Other bentonite		
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 2 ft. to 6 ft. From ft. to 2 ft.									
What is the nearest source of possible contamination:						10 Livestock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines			ral lines	7 Pit privy		11 Fuel	storage 15	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			s pool	8 Sewage lagoon			ilizer storage 16	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							cticide storage None	e Apparent	
Direction from well?  How many feet?									
FROM	ТО		LITHOLOGIC LOC	3	FROM	то	PLUGGING INTE		
					0	2	compacted tops	oil	
					2	6	cement grout		
					6	22	bentonite hole		
					22	24	chlorinated san	nd and gravel	
								7 M 1	
				W			1700		
					L				
							14-2		
					<u> </u>		7-10-11-11-11-11-11-11-11-11-11-11-11-11-	7-5-7	
							741		
					<u> </u>				
7 CONT	TRACTO	OR'S OR LANDOWNE	er's certification: 1	his water well was (1	) construct	ed, (2) recons	structed, or (3) plugged under	my jurisdiction and	
was cor	mpleted	on (mo/day/year	r)Q6/10/	/1996	and this rec	ord is true to	the best of my knowledge an	d belief. Kansas Water	
Well Co	ntracto	r's License No	236	This Water Well Re	cord was c	ompleted on	(mo/day/yr)	2/96	
Under t	he busi	ness name of.从	arb™ett™¢	Pump Servi	ceii	າຕ by (si	gnature)	9 92	
							Jodd	S. Harp	