.l		TER WELL RECORD	Form WWC-5			
LOCATION OF W			i	ction Number	Township Number	Range Number
County: Sedgwic		1/4 NW 1/4 SW		25	T 27 S	R 1 (E#W
_	on from nearest town or city street		ea within city?			
	340 S. Oliver, Wichit	a, KS				
2 WATER WELL O						
	30x Quik Trip Corporat				•	e, Division of Water Resources
	 1862 Craigshire Dr 					
J LOCATE WELL'S AN "X" IN SECTION	LOCATION WITH 4 DEPTH OF	COMPLETED WELL	25	ft. ELEVAT	TION:	
AN A IN SECTION	N Depth(s) Grou	ndwater Encountered	20	ft. 2	 ft	. 3
ī !	I WELL'S STAT	IC WATER LEVEL !	5.84. ft. b	elow land surf	ace measured on mo/day	^{/yr} 11/7/96······
₹ NW	Pu	mp test data: Well wate	er was	ft. af	ter hours	pumping gpm
[] [7 ⁻ N ₁ - 1	Est. Yield	gpm: Well water	er was	ft. af	ter hours	pumping gpm
<u> </u>	Bore Hole Dia	meter . 8 . 625in. to	25	ft., a	ınd <u></u>	.in. to <u></u>
₹ W 🗶 I		R TO BE USED AS:	5 Public water	er supply	8 Air conditioning	11 Injection well
sw	1 Domest					2 Other (Specify below)
] 3W	2 Irrigatio	n 4 Industrial	7 Lawn and	garden only 🚺	0) Monitoring well . か. 仏	1-1
	l Was a chemic					es, mo/day/yr sample was sub-
1	\$ mitted			Wat	er Well Disinfected? Yes	No X
5 TYPE OF BLANK	CASING USED:	5 Wrought iron	8 Concr			ued Clamped
Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other	(specify below) W	elded
(2)PVC	4 ABS	7 Fiberglass			т	readed
Blank casing diamete	er . 3 in. to 15	ft., Dia	in. to		ft., Dia	in. to 🗴 ft.
	land surface \mathcal{O}	in weight		The /f	t. Wall thickness or gauge	
l	OR PERFORATION MATERIAL:	SCE	I 40 ₽У\$ _∨	С	10 Asbestos-ce	
1 Steel	3 Stainless steel	5 Fiberglass	8 RM	IP (SR)	11 Other (spec	ify)
2 Brass	4 Galvanized steel	•	9 AB		12 None used	
SCREEN OR PERFO	ORATION OPENINGS ARE:		ed wrapped		8 Saw cut	11 None (open hole)
1 Continuous s	slot (3) Mill slot		wrapped		9 Drilled holes	` '
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From ft. to						
>nD From						
						t. to
	From /	ft. to		ft., From	1 f	t. to ft.
6 GROUT MATERIA	AL; 1 Neat cement	2 Cement grout	r (3 Bento	nite . / 4 (Other	
Grout Intervals: Fr	rom. 0	ft., From	12 ft.	to. 1. 4	ft., – From -	ft. to ft.
	source of possible contamination:			10 Livest		Abandoned-water well
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel s	torage 15	Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lag	oon	12 Fertiliz	er storage	Other (specify below)
3 Watertight se	ewer lines 6 Seepage pit	9 Feedyard			cide storage	
Direction from well?		•		How man	v feet? Conta	minated Si
FROM TO	LITHOLOGI	C LOG	FROM	ТО		INTERVALS
GL 1.00	Concrete, fill					
1.00 25.00	Silty Clay (CL)					
5.00 TD	End of Borehole					
3100	DE OF BOLEHOTE					
					7 100	
						THE PARTY OF THE P
				F1	ush Mount	
				1 1	iver	
				n .	Taylor	
	1					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) Senstructed (2) reconstructed, (2) plugged under my jurisdiction and was						
completed on (mo/day/year) 11-7-96 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contracto	or's License No	This Water W	Vell Record wa	s completed o	n (mo/day/w/)	0-76
under the business r	name of			by (signatu	ire) Donsin	for Varin Hins
INSTRUCTIONS: Use of Health and Environ	typewriter or ball point pen. PLEASE PRESS nment, Bureau of Water, Topeka, Kansas 66	S FIRMLY and <u>PRINT</u> clearly. Plo 620-0001. Telephone: 913-296-5	ease fill in blanks, 5545. Send one to	underline or circle WATER WELL OW	the correct unswers. Send top the NER and retain one for your reco	rea copies to Kansas Department ords.