1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-	KSA 82a-1212 Section Number	Township Number	Range Number	
		WW C1			_	157	
Sedgwick	SE 1/4	NW 1/4 SI	E 1/4	8	т 27 s	R 1E E/W	
Distance and direction from nearest town or city street address of well if located within city?							
1651 S. Waco Wichita, Kansas							
	Stephen						
RR#, ST. ADRESS, BOX#: 1651 S. Waco Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:							
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COLUMN WELL 25 ft. ELEVATION:							
AN "X" IN SECTION BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
l i [w	ELL'S STATIC W	ATER LEVEL 13	FT	BELOW LAND SU	RFACE MEASURED ON mo/day/yr	01/29/1997	
	Pump tes	_	ater was	ft.	after hours pum	-	
NWNE	. Yield		ater was	ft.	after hours pum		
¥	re Hole Diameter 4	BF		ft.	and in.	to ft.	
E BOI	ELL WATER		to Public wate			njection well	
			Oil field wa			ther (Specify below)	
sw	1 Domestic				ě	dier (spechy below)	
	2 Irrigation		Lawn and g		10 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was							
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	lued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement	t 9	Other (Specify b	elow) W	'elded	
2 PVC 4 ABS		7 Fiberglass			T	hreaded X	
Blank casing Diameter 1 1/4 in.	to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height accertand surface 60	in.,	weight	ш		Wall thickness or gauge No.	14.	
TYPE OF SCREEN OR PERFORATIO	N MATERIAL:	weight		PVC	10 Asbestos-ceme	nt	
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify)) at / n	
2 Brass 4 Galvanized steel		6 Concrete tile		ABS	12 None used (op	N/A	
1	VO 4 P.Z			ADS	8 Saw cut	11 None (open hole)	
SCREEN OR PERFORATION OPENIN	NG ARE:		d wrapped			11 None (open note)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punch		7 Torch	cut		10 Other (specify)	'A	
SCREEN-PERFORATION INTERVAL	S: from	ft. t	to	ft., From	ft. to	ft.	
	from	ft. (to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from		ft. to		ft., Fron	ft. to	ft.	
	from	ft. 1	to	ft., Fron	ı ft. to	ft	
6 GROUT MATERIAL: 1 Neat cem	ent 2 C	Cement grout	3 Be	ntonite	4 Other bentonite	hole plug	
Grout Intervals: From O	. to 6	ft. From	ft.	to	ft. From 6	ft. to 20 ft.	
What is the nearest source of possible contamination:				10 Livestock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines		7 Pit privy	7 Pit privy		uel storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertiliz		16 Other (specify below)	
12 Importante atomore				alda atamaga			
L							
Direction from well? How many feet? FROM TO PLUGGING INTERVALS							
FROM 10 LII	HOLOGIC LOG		FROM	TO		(VALS	
			0		cement grout	. 1	
		1760	6		bentonite hole		
			20	25	chlorinated san	d and gravel	
			<u> </u>				
	1.104						
			1	1 1			
						1	
	**			<u> </u>			
			<u> </u>				
			<u> </u>				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No	36	This Water Well Re	cord was c	ompleted on (m	ю/day/yr)Ω1./.3.J	L/.9.7	
Under the business name of HarpWell&PumpServiceInc by (signature)							
Todd S. Harp							

...