[]	A TED MET	EDICTION	Water Well Re	cord Form WWC-		T	Range Number	
1 LOCATION OF W		FRACTION	G19 ···	C15	Section Number	Township Number	110	
Sedgwick NW 1/4 Distance and direction frem nearest town or city street address of well if locate			SE 1/4	SE 1/4	17	T 27 s	R 1E E/W	
141 W. Elm Street Wichita, Kansas WATER WELLOWNER: WICHITA, CITY OF								
RRM, ST. ADRESS		O.E.			Board of Agriculture, Divivsion of Water Resource			
CITY, STATE, ZIP CODE: Wichita, Kansa			67203		Application Number: T970086			
LOCATE WELL'S	LOCATION WITH	DEPTH OF COM				VATION:	_	
AN "X" IN SECTIO	N	Depth(s) groundwa			ft.	2 ft.	3 ft.	
		WELL'S STATIC W. Pump test		18 rı ili water was		FACE MEASURED ON mo/day/yr Ifter hours pum	02/28/1997	
NW.	NE	Est. Yield		ell water was		after hours pum		
§ w −−−	1 1 1 1	Bore Hole Diameter	12 in.	to 45	ſt.	and in.	to ft.	
= "		WELL WATER TO I		5 Public water			njection well	
sw.		1 Domestic	3 Feedlot 4 Industrial	6 Oll field w	•••		Other (Specify below)	
		2 Irrigation		7 Lawn and	•	O Monitoring well	no/day/yr sample was	
'	S	Was a chemical/bacte submitted	riologicai sample	e submitted to D	-	er Well Disinfected? Yes		
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded							Velded	
2 PVC	4 ABS		7 Fiberglass	S	DR-26		Threaded	
Blank casing Diar	•	in. to 20	ft., Dia			ft., Dia in.	to ft.	
Casing height above land surface 12 in., TYPE OF SCREEN OR PERFORATION MATERIAL:				5.52	lbs. / ft. '7 7 PVC	Wall thickness or gauge No. 10 Asbestos-cem	.332	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass	4 Galvanized steel	I	6 Concrete tile		9 ABS	12 None used (o	pen hole)	
1	REFORATION OPE	NING ARE:		5 Gauzed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot	3 Mill slo			Vire wrapped		9 Drilled holes		
2 Louvered shutt	• •			orch cut		10 Other (specify)	~	
SCREEN-PERFO	DRATION INTERV		ft. to 40	ft., From		ſL.		
GRAVEL PACK INTERVALS: from 20)	ft. to ft. to 45	ft., From ft., From		ft. ft.	
from			ft. to		ft., From		<u> </u>	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hold Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to							e hole plug	
Grout Intervals:		ft. From	ft. From ft. to		ft. From	ft. to ft.		
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines			7 Pit privy		10 Livesto 11 Fuel ste		Abandon water well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon			p 15	15 Oil well/Gas well 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Appare							`• • /	
Direction from well?								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 2 2 5	topsoil clay	<u> </u>						
5 15	silty sa	nd			- -			
15 38		o coarse s	and					
38 45	blue sha							
	-							
	·							
			· · · · · · · · · · · · · · · · · · ·					

					_			
			 		_			
	-							
7 CONTRACT	L		In			usted or /3\ minmed	mu juriodistian	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contractor's License No23.5								
Under the business name of Harp Well & Pump Service. Inc by (signature)								
Todd S. Harp								